



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION
11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/economy

NOTICE OF ACCEPTANCE (NOA)

GAF
1 Campus Drive
Parsippany, NJ 07054

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: EnergyGuard™ Polyiso Insulation, EnergyGuard™ HD Polyiso Insulation, EnergyGuard™ HD Plus Polyiso Insulation, EnergyGuard™ Ultra Polyiso Insulation.

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA No.15-0129.16 and consists of pages 1 through 5.
The submitted documentation was reviewed by Gaspar J Rodriguez.



NOA No.: 15-0812.17
Expiration Date: 02/28/18
Approval Date: 04/28/16
Page 1 of 5

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Insulation
Material: Polyisocyanurate

SCOPE:

This approves EnergyGuard™ Polyiso Insulation, EnergyGuard™ Tapered Polyiso Insulation, EnergyGuard™ HD Polyiso Insulation, EnergyGuard™ HD Plus Polyiso Insulation, EnergyGuard™ Ultra Polyiso Insulation and EnergyGuard™ Ultra Tapered Polyiso Insulation as manufactured by GAF as described in this Notice of Acceptance. These products have been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone of the Florida Building Code.

TYPICAL PHYSICAL PROPERTIES:

| EnergyGuard™ Polyiso Insulation | | |
|---|-------------|---|
| <u>Property</u> | <u>Test</u> | <u>Typical Results</u> |
| Overall Density | ASTM D 1622 | 2.5 lbs./ft. ³ |
| Compressive Strength | ASTM D 1621 | 24 PSI |
| Water Absorption | ASTM C 209 | Less than 1% by volume |
| Moisture Vapor Transmission | ASTM E 96 | Less than one (1) perm |
| Surface Burning Characteristics (4" Foam Core Max.) | ASTM E 84 | Flamespread: 45 Smoke Developed: 105 |

| EnergyGuard™ Ultra Polyiso Insulation | | |
|---|-------------|---|
| <u>Property</u> | <u>Test</u> | <u>Typical Results</u> |
| Overall Density | ASTM D1622 | 4.47 lbs./ft. ³ |
| Compressive Strength | ASTM D1621 | 24 PSI |
| Water Absorption | ASTM C209 | Less than 1% by volume |
| Moisture Vapor Transmission | ASTM E96 | Less than two (2) perm |
| Surface Burning Characteristics (4" Foam Core Max.) | ASTM E84 | Flamespread: 45 Smoke Developed: 105 |

| EnergyGuard™ HD Polyiso Insulation | | |
|--|-------------|---|
| <u>Property</u> | <u>Test</u> | <u>Typical Results</u> |
| Overall Density | ASTM D1622 | 9.5 lbs./ft. ³ |
| Compressive Strength | ASTM D1621 | 81PSI |
| Water Absorption | ASTM C209 | Less than 1% by volume |
| Moisture Vapor Transmission | ASTM E96 | Less than two (2) perm |
| Surface Burning Characteristics (½" thick) | ASTM E84 | Flamespread: 65 Smoke Developed: 110 |

| EnergyGuard™ HD Plus Polyiso Insulation | | |
|--|-------------|---|
| <u>Property</u> | <u>Test</u> | <u>Typical Results</u> |
| Overall Density | ASTM D1622 | 9.9 lbs./ft. ³ |
| Compressive Strength | ASTM D1621 | 122 PSI |
| Water Absorption | ASTM C209 | Less than 2% by volume |
| Moisture Vapor Transmission | ASTM E96 | Less than one (1) perm |
| Surface Burning Characteristics (½" thick) | ASTM E84 | Flamespread: 65 Smoke Developed: 110 |

Note: The physical properties listed above are presented at typical average values as determined by accepted ASTM test methods and are subject to normal manufacturing variation. Numerical ratings as determined by ASTM Test Method E-84 are not intended to reflect hazards presented by this or any other material under actual fire conditions.



NOA No.: 15-0812.17
 Expiration Date: 02/28/18
 Approval Date: 04/28/16
 Page 2 of 5

EVIDENCE SUBMITTED

| <u>Test Agency</u> | <u>Test Identifier</u> | <u>Test Specification</u> | <u>Date</u> |
|-------------------------------------|---|---------------------------|-----------------------|
| Factory Mutual Research Corporation | 3045789 | 4470 | 07/12/12 |
| | 3042905 | 4470 | 01/10/12 |
| | 3038278 | 4470 | 11/18/11 |
| | 3041005 | 4470 | 05/31/11 |
| | 3041746 | 4470 | 08/17/11 |
| | 3045176 | 4470 | 10/12/12 |
| | 3046328 | 4470 | 09/13/12 |
| | 3041769 | 4470 | 05/26/12 |
| | 3024805 | 4470 | 11/20/06 |
| | 3044914 | 4470 | 06/18/12 |
| | 3045166 | 4470 | 07/24/12 |
| | 3036980 | 4470 | 08/14/09 |
| | PRI Construction Materials Technologies LLC | GAF-369-02-01 | ASTM C1289/ASTM D1622 |
| GAF-411-02-01 | | ASTM C1289/ASTM D1622 | 05/02/13 |
| GAF-412-02-01 | | ASTM C1289/ASTM D1622 | 05/02/13 |
| GAF-409-02-01 | | ASTM C1289/ASTM D1622 | 05/28/13 |
| GAF-417-02-01 | | ASTM C1289/ASTM D1622 | 05/28/13 |
| GAF-464-02-01 | | ASTM C1289/ASTM D1622 | 02/06/14 |
| GAF-580-02-01 | | ASTM C1289/ASTM D1622 | 07/23/15 |
| GAF-581-02-01 | ASTM C1289/ASTM D1622 | 07/23/15 | |
| UL LLC | 12CA42043 | UL723 | 10/29/12 |
| | 12NK15055 | UL790 | 03/27/13 |
| | 13CA46760 | UL723 | 09/09/13 |
| | 12NK15055 | UL790 | 03/01/13 |
| | 4787285972 | UL723/E84 | 02/01/16 |

MANUFACTURING LOCATIONS:

- Statesboro, GA:**
 - EnergyGuard™ Polyiso Insulation
 - EnergyGuard™ Tapered Polyiso Insulation
 - EnergyGuard™ Ultra Polyiso Insulation
 - EnergyGuard™ Ultra Tapered Polyiso Insulation
 - EnergyGuard™ HD Polyiso Insulation
 - EnergyGuard™ HD Plus Polyiso Insulation
- Gainesville, TX:**
 - EnergyGuard™ Polyiso Insulation
 - EnergyGuard™ Tapered Polyiso Insulation
 - EnergyGuard™ HD Polyiso Insulation
 - EnergyGuard™ HD Plus Polyiso Insulation



PRODUCT DESCRIPTION:

Tradename: EnergyGuard™ Polyiso Insulation
Thickness: 0.5" (12 mm) to 4.0" (102 mm)
Board Size(s): 48" x 48" and 48" x 96" (1220 x 1220 to 2400 mm)
Core: Polyisocyanurate
Facers: Reinforced glass fiber/organic felt
Special Application: See specific Roof Assembly Notice of Acceptance for approved assemblies.

Tradename: EnergyGuard™ Tapered Polyiso Insulation
Thickness: 0.5" (12 mm) to 4.0" (102 mm)
Board Size(s): 48" x 48" (1220 x 1220 mm)
Core: Polyisocyanurate
Facers: Reinforced glass fiber/organic felt
Special Application: See specific Roof Assembly Notice of Acceptance for approved assemblies.

Tradename: EnergyGuard™ Ultra Polyiso Insulation
Thickness: 0.5" (12 mm) to 4.0" (102 mm)
Board Size(s): 48" x 48" and 48" x 96" (1220 x 1220 to 2400 mm)
Core: Polyisocyanurate
Facers: Coated glass fiber
Special Application: See specific Roof Assembly Notice of Acceptance for approved assemblies.

Tradename: EnergyGuard™ Ultra Tapered Polyiso Insulation
Thickness: 0.5" (12 mm) to 4.0" (102 mm)
Board Size(s): 48" x 48" (1220 x 1220 mm)
Core: Polyisocyanurate
Facers: Coated glass fiber
Special Application: See specific Roof Assembly Notice of Acceptance for approved assemblies.

Tradename: EnergyGuard™ HD Polyiso Insulation
Thickness: 0.5" (12 mm)
Board Size(s): 48" x 48" and 48" x 96" (1220 x 1220 to 2400 mm)
Core: Polyisocyanurate
Facers: Coated glass fiber
Special Application: See specific Roof Assembly Notice of Acceptance for approved assemblies.

Tradename: EnergyGuard™ HD Plus Polyiso Insulation
Thickness: 0.5" (12 mm)
Board Size(s): 48" x 48" and 48" x 96" (1220 x 1220 to 2400 mm)
Core: Polyisocyanurate
Facers: Coated glass fiber
Special Application: See specific Roof Assembly Notice of Acceptance for approved assemblies.



LIMITATIONS:

1. Fire classification is not a part of this Notice of Acceptance
2. Roof assemblies are approved under specific Roof Assembly Product Control Notice of Acceptance.
3. GAF products may be used with any approved roof covering listing a specific GAF component as part of its Roof Assembly Notice of Acceptance. If a GAF product is not listed, a request may be made to the authority having jurisdiction or the Miami Dade Product Control Section for approval provided that appropriate documentation is provided.
4. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list the products listed herein as part of their Roof Assembly Notice of Acceptance. See roof system Notice of Acceptance (NOA) for application rates and uses.
5. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to Miami-Dade County Product Control upon request.
6. Change in materials, use, or manufacture of any products listed herein shall be cause for termination of this Notice of Acceptance.
7. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.
8. All approved products listed herein shall be labeled and shall bear the imprint or identifiable marking of the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



END OF THIS ACCEPTANCE



NOA No.: 15-0812.17
Expiration Date: 02/28/18
Approval Date: 04/28/16
Page 5 of 5