



**NOTE:**

1. FOR INSULATION THICKNESS GREATER THAN 8" (203 mm), A HARD BOARD IS REQUIRED ON MECHANICAL SYSTEMS ONLY
2. IF EVERGUARD® FREEDOM™ MEMBRANE IS USED, BONDING ADHESIVE IS NOT NEEDED AND WALL MUST BE PRIMED.
3. 25 YEAR GUARANTEES AND ABOVE MUST USE EXTREME ACCESSORIES
4. FLASHINGS MAY BE ADHERED OR INSTALLED DRY. SEE MANUAL FOR DIMENSIONS.
5. INSIDE CORNERS MAY ALSO BE FIELD-FABRICATED USING UNREINFORCED MEMBRANE.
6. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES (REFER TO EVERGUARD® DETAIL 115).



**EverGuard**  
SINGLE-PLY ROOFING SYSTEMS  
PARAPET WALL &  
CURB SERIES

DRAWING #  
**327A**

**INSIDE CORNER REINFORCEMENT-  
PREFORMED CORNER DETAIL**

THIS DETAIL APPLIES TO:

**ALL SYSTEMS**

www.gaf.com  
1 Campus Drive,  
 Parsippany, NJ 07054

SCALE  
N.T.S.

REVISION DATE  
6-20-16