



**NOTE:**

1. FOR INSULATION THICKNESS GREATER THAN 8" (203 mm), A HARD BOARD IS REQUIRED.
2. FOR SELF-ADHERED RAPIDSEAM™ TECHNOLOGY SYSTEMS, SEE EVERGUARD® DETAIL 330 FOR LAP APPLICATION.
3. IF EVERGUARD® FREEDOM™ MEMBRANE IS USED, BONDING ADHESIVE IS NOT NEEDED AND WALL MUST BE PRIMED.
4. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES (REFER TO EVERGUARD® DETAIL 115).

 <small>www.gaf.com</small> <small>1 Campus Drive,</small> <small>Parlisppany, NJ 07054</small>	 <b>EverGuard</b> <small>SINGLE-PLY ROOFING SYSTEMS</small> <b>ROOF PENETRATION</b> <b>SERIES</b>	DRAWING # <b>503B</b>	<b>TERMINATION AT EXISTING R.T.U.</b> <b>WITH COUNTERFLASHING DETAIL</b>	THIS DETAIL APPLIES TO: <b>ALL SYSTEMS</b>
		SCALE <b>N.T.S.</b>		REVISION DATE <b>6-21-16</b>