


**NOTE:**

1. FOR EXTENDED WARRANTY, COUNTERFLASHING MUST BE USED. SEE EVERGUARD® DETAIL 301.
2. FOR INSULATION THICKNESS GREATER THAN 8" (203 mm), A HARD BOARD IS REQUIRED ON MECHANICAL SYSTEMS ONLY.
3. FOR 15-YR. WARRANTY, ADD FLEXSEAL™ CAULK GRADE SEALANT BEHIND COATED METAL. ADD TERMINATION BAR EVEN WITH TOP OF COATED METAL. SECURE BAR 12" (305 mm) O.C. AND ADD FLEXSEAL™ CAULK GRADE SEALANT IN A BEAD SO THAT BOTH COATED METAL AND TERMINATION BAR ARE COVERED.
4. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES (REFER TO EVERGUARD® DETAIL 115).



**EverGuard**  
SINGLE-PLY ROOFING SYSTEMS  
PARAPET WALL &  
CURB SERIES

DRAWING #  
**308**  
SCALE  
N.T.S.

**COATED METAL WALL  
FLASHING DETAIL**

THIS DETAIL APPLIES TO:  
**ALL SYSTEMS**  
REVISION DATE  
6-20-16