

# Ruberoid® EnergyCap Heat-Weld 250 Plus FR

## Material Safety Data Sheet

Updated: 6/09



*Quality You Can Trust Since 1886...  
From North America's Largest Roofing Manufacturer™*



**SECTION 1: PRODUCT AND COMPANY INFORMATION**

**PRODUCT NAME:** Ruberoid® EnergyCap Heat-Weld 250 Plus FR

**TRADE NAME:** N/A

**CHEMICAL NAME / SYNONYM:** N/A

**CHEMICAL FAMILY:** Modified Bitumen Roll Roofing

**MANUFACTURER:** GAF Materials Corporation

**ADDRESS:** 1361 Alps Road, Wayne, NJ 07470

**24-HOUR EMERGENCY PHONE (CHEMTREC):** 800 – 424 – 9300

**INFORMATION ONLY:** 800 – 766 – 3411

**PREPARED BY:** Corporate EHS

**APPROVED BY:** Corporate EHS

**NFPA Hazard Rating**

**HMIS Hazard Rating**

Health	1
Flammable	1
Reactive	0
Special Hazards	-

1  
1  
0  
-

Health	1
Flammable	1
Reactive	0
Personal Protection	X

1  
1  
0  
X

**OSHA HAZARDOUS:** Yes

**No**

**SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

**OCCUPATIONAL EXPOSURE LIMITS**

CHEMICAL NAME	CAS #	%(BY WT)	OSHA	ACGIH	OTHER
<b>MODIFIED BITUMINOUS BLEND</b>					
Asphalt (Bitumen)	8052-42-4	20 - 30	0.5 mg/m <sup>3</sup> as benzene-soluble aerosol	NE	REL: 5 mg/m <sup>3</sup> ceil 15-min

## OCCUPATIONAL EXPOSURE LIMITS

CHEMICAL NAME	CAS #	% (BY WT)	OSHA	ACGIH	OTHER
Styrene Butadiene Copolymer	9003-55-8	4 - 8	NE	NE	NE
Calcium Borate	12007-56-6	18 - 24	NE	NE	NE

**REINFORCEMENT**  
Polyester or a mix of polyester and glass roving

Polyester Mat	100684-92-2	2 - 8	NE	NE	NE
Fiberglass roving	65997-17-3	0.5 - 2	NE	1 f/cc	REL: 3/fcc TWA

**Back and Top Surfacing**

Polypropylene film	9003-07-0	0.01 - 1	NE	NE	NE
Polyethylene film	9002-88-4	0.01 - 1	NE	NE	NE
Granules	14808-60-7	20 - 30	10 mg/m <sup>3</sup> / (% SiO <sub>2</sub> + 2) – resp.	0.025 mg/m <sup>3</sup>	REL: 0.05 mg/m <sup>3</sup> – resp.
Acrylic Polymer	9003-01-4	2 - 6	NE	NE	NE

Footnotes:

**NE= Not Established****SECTION 3: HAZARDS IDENTIFICATION****PRIMARY ROUTE OF EXPOSURE:** Inhalation**SIGNS & SYMPTOMS OF EXPOSURE** N/A**EYES:** During application asphalt fumes may be emitted and may cause minor eye irritation. Flush eyes with flowing water for 15 mins.**SKIN:** During application asphalt fumes may be emitted and may cause minor skin irritation. Contact with molten asphalt at high temperatures can cause thermal burns. Cool with ice or water.**INGESTION:** Exposure is not likely to occur but if it does get medical advice.**INHALATION:** During application asphalt fumes may be emitted and may cause minor irritation of nasal passages, throat and lungs. Can cause headaches and nausea.**ACUTE HEALTH HAZARDS:** Nasal irritant of mucus membranes.**CHRONIC HEALTH HAZARDS:** Asphalt: burns or nasal/throat irritation.

---

CARCINOGENICITY: N/A

---

**SECTION 4: FIRST AID MEASURES**

---

**FIRST AID PROCEDURES**

**EYES:** Flush with water for 15 minutes. Remove contact lenses if worn. Consult with medical personnel if irritation persists.

**SKIN:** Do not attempt to remove asphalt immediately. Cover with Vaseline. Remove when asphalt has softened.

**INHALATION:** Remove to fresh air. Seek medical assistance if needed.

**INGESTION:** N/A

**NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:** N/A

---

**SECTION 5: FIRE-FIGHTING PROCEDURES**

---

**SUITABLE EXTINGUISHING MEDIA:** Water spray, carbon dioxide, dry chemical or foam.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide, carbon dioxide, acrolein, acids, ketones, aldehydes, hydrogen sulfide.

**RECOMMENDED FIRE FIGHTING PROCEDURES:** Self-contained breathing apparatus and full protective clothing recommended.

**UNUSUAL FIRE & EXPLOSION HAZARDS:** None.

---

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

---

**ACCIDENTAL RELEASE MEASURES:** None

---

**SECTION 7: HANDLING AND STORAGE**

---

**HANDLING AND STORAGE:** Long sleeve shirt and long trousers. Solid work shoes. When heated small amounts of Hydrogen Sulfide may be given off. Hydrogen Sulfide is flammable, toxic gas and breathing fumes must be avoided.

**OTHER PRECAUTIONS:** N/A

---

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

<b>ENGINEERING CONTROLS / VENTILATION:</b>	Use sufficient ventilation.
<b>RESPIRATORY PROTECTION:</b>	N/A
<b>EYE PROTECTION:</b>	Safety glasses with side shields.
<b>SKIN PROTECTION:</b>	Long sleeves, trousers and gloves.
<b>OTHER PROTECTIVE EQUIPMENT:</b>	When handling this material, wear long sleeve shirts, long pants and safety shoes.
<b>WORK HYGIENIC PRACTICES:</b>	Washing of hands is recommended after handling coated sheets.
<b>EXPOSURE GUIDELINES:</b>	N/A

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>APPEARANCE &amp; ODOR:</b>	Thin black sheet in roll form, granule, talc, fillers, sand, film surfaced or white acrylic coated. Slight asphaltic odor.		
<b>FLASH POINT:</b>	>500 °F	<b>LOWER EXPOSURE LIMIT:</b>	No Data
<b>METHOD USED:</b>	COC	<b>UPPER EXPLOSIVE LIMIT:</b>	No Data
<b>EVAPORATION RATE:</b>	No Data	<b>BOILING POINT:</b>	No Data
<b>Ph (undiluted product):</b>	No Data	<b>MELTING POINT:</b>	No Data
<b>SOLUBILITY IN WATER:</b>	No	<b>SPECIFIC GRAVITY:</b>	No Data
<b>VAPOR DENSITY:</b>	No Data	<b>PERCENT VOLATILE:</b>	No Data
<b>VAPOR PRESSURE:</b>	No Data	<b>MOLECULAR WEIGHT:</b>	No Data
<b>VOC WITH WATER (LBS/GAL):</b>	No Data	<b>WITHOUT WATER (LBS/GAL):</b>	No Data

**SECTION 10: STABILITY AND REACTIVITY**

<b>THERMAL STABILITY:</b>	<b>STABLE</b> X	<b>UNSTABLE</b> <input type="checkbox"/>
<b>CONDITIONS TO AVOID (STABILITY):</b>	N/A	
<b>INCOMPATIBILITY (MATERIAL TO AVOID):</b>	N/A	

**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Carbon monoxide, carbon dioxide, acrolein, acids, ketones, aldehydes, hydrogen sulfide.

**HAZARDOUS POLYMERIZATION:** Will not occur.

---

**SECTION 11: TOXICOLOGICAL INFORMATION**

---

**TOXICOLOGICAL INFORMATION:** Hydrogen Sulfide is flammable, toxic gas and breathing fumes must be avoided.

---

**SECTION 12: ECOLOGICAL INFORMATION**

---

**ECOLOGICAL INFORMATION:** No information available.

---

**SECTION 13: DISPOSAL CONSIDERATIONS**

---

**WASTE DISPOSAL METHOD:** This product, as supplied, is not regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. Comply with state and local regulations for disposal.

**RCRA HAZARD CLASS:** None

---

**SECTION 14: TRANSPORT INFORMATION**

---

**U.S. DOT TRANSPORTATION**

**PROPER SHIPPING NAME:** This product is not classified as a hazardous material for transport.

**HAZARD CLASS:** N/A

**ID NUMBER:** N/A

**PACKING GROUP:** N/A

**LABEL STATEMENT:** N/A

**OTHER:** N/A

---

**SECTION 15: REGULATORY INFORMATION**

---

**U.S. FEDERAL REGULATIONS**

**TSCA:** This product and its components are listed on the TSCA 8(b) inventory.

**CERCLA:** N/A

**SARA**

**311/312 HAZARD CATEGORIES:** N/A

**313 REPORTABLE INGREDIENTS:** N/A

**CALIFORNIA PROPOSITION 65:** N/A

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

Chemical Name	CAS #	CA	MA	MN	NJ	PA	RI
Asphalt (Bitumen)	8052-42-4	Yes	Yes	N/A	Yes	Yes	Yes
Styrene Butadiene Copolymer	9003-55-8	No	No	N/A	No	No	No
Calcium Borate	12007-56-6	No	No	N/A	No	No	No
Polyester Mat	100684-92-2	No	No	N/A	No	No	No
Fiberglass roving	65997-17-3	No	No	N/A	No	No	No
Polypropylene film	9003-07-0	No	No	N/A	No	No	No
Polyethylene film	9002-88-4	No	No	N/A	No	No	No
Granules	14808-60-7	Yes	Yes	Yes	Yes	Yes	Yes
Acrylic Polymer	9003-01-4	No	No	N/A	No	No	No

**SECTION 16: OTHER INFORMATION**

**ADDITIONAL COMMENTS:** None.

**DATE OF PREVIOUS MSDS:** June 2003

**CHANGES SINCE PREVIOUS MSDS:** Changed to the ANSI 16 section MSDS format.

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It

is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.