

RUBEROID® Mop Plus Smooth Membrane

Updated: 8/16



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*



RUBEROID®

MOP PLUS SMOOTH MEMBRANE

Description

RUBEROID® Mop Plus Smooth Membrane is a premium, heavy-duty, modified bitumen membrane manufactured to stringent GAF specifications. Its core is a strong, resilient non-woven polyester mat that is coated with flexible SBS polymer modified asphalt and has a smooth surface. *Smooth-surface mop-applied installations must be protected with surfacing.*

Uses

RUBEROID® Mop Plus Smooth Membrane is designed for new roofing and reroofing applications as well as the construction of flashings. RUBEROID® Mop Plus Smooth Membrane is also an ideal product for repairs of built-up roofing membranes or other modified bitumen systems.

Advantages

- Guarantees are available for up to 20 years.*
- Light weight—Installed roof designs weigh less than 2 pounds per square foot (9.8 kg/m²).
- Durable—Specially formulated modified asphalt gives RUBEROID® Mop Plus Smooth Membrane lasting performance.

Advantages (Continued)

- Resilient—RUBEROID® Mop Plus Smooth Membrane's heavyweight polyester mat core allows it to resist splits and tears due to its pliability and elongation characteristics.
- RUBEROID® Mop Plus Smooth Membrane is manufactured by GAF, a company with over 125 years in the roofing business.



Applicable Standards

Meets ASTM D6164, Type II, Grade S
FM Approved
ICC ESR-1274 Pending
UL/ULC Listed

Product Specifications (nominal)

Roll Size	1 square (107.5 gross sq. ft.) (9.9 m ²)
Roll Length	32.56' (9.9 m)
Roll Width	39.625" (1006.5 mm)
Approx. Roll Weight	80 lb (36.29 kg)
Product Thickness	0.120" (3.05 mm)

This product meets or exceeds the following ASTM D6164, Type II, Grade S, minimum requirements:

Property	Test Method	Value
Tensile Strength @ 0°F (min), lbf/in	ASTM D5147	100
Elongation @ 0°F (min), %	ASTM D5147	20
Low Temperature Flexibility (max), °F	ASTM D5147	0
Tear Strength (min), lbf	ASTM D5147	70
Dimensional Stability, (max) %	ASTM D5147	1