



NOTE:

1. MASONRY WALLS TO BE PRIMED PRIOR TO FLASHING. WOOD WALLS REQUIRE BASE SHEET NAILED TO WALL 8" (203 mm) O.C. ALONG TOP AND LAPS AND 8" (203 mm) O.C. THROUGHOUT THE FIELD OF THE BASE SHEET ON THE WALL.
2. WALL COVERINGS TURNED OVER EDGE A MINIMUM OF 1 1/2" (38mm) OR THICKNESS OF NAILER WHICHEVER IS GREATER.
3. FASTEN BASE FLASHING APPROXIMATELY 8" (203 mm) O.C. FOR HEIGHTS UP TO 12" (305 mm) AND 4" (102 mm) O.C. FOR HEIGHTS UP TO 24" (610 mm).
4. FOR WALL FLASHINGS IN EXCESS OF 4' (1.22 m) CONTACT GAF TECHNICAL SERVICES AT 1-800-ROOF-411.



GAFGLAS
 Built-Up Roofing Systems
RUBEROID
 Modified Bitumen Roofing Systems

**ALTERNATE HIGH PARAPET
 WALL DETAIL**

DRAWING #

07

SYSTEM

MB/BUR

WWW.GAF.COM
 1 Campus Drive.
 Parsippany, NJ
 07054

SCALE

N.T.S.

ISSUE/ REVISION DATE

7-01-14