

# **RUBEROID® ULTRACLAD® SBS Membrane**

Updated: 8/16



*Quality You Can Trust...From  
North America's Largest Roofing Manufacturer!™*



# RUBEROID® ULTRACLAD® SBS MEMBRANE



## Description

RUBEROID® UltraClad® SBS Membrane is a premium, fire-retarding aluminum foil-faced bitumen membrane manufactured to stringent GAF specifications. RUBEROID® UltraClad® SBS Membrane is manufactured using a high-tensile woven fiberglass scrim coated with an SBS modified asphalt, which provides excellent cold temperature flexibility and elongation properties. The membrane is covered with a protective foil facing with small built-in control channels.

## Uses

RUBEROID® UltraClad® SBS Membrane is designed for new roofing and reroofing applications where long-term flashing and roof system performance is specified. RUBEROID® UltraClad® SBS Membrane can be applied using heat-welding methods.

## Advantages

- Guarantees are available for up to 20 years.\*

## Advantages (Continued)

- SBS modifier provides flexibility for easy installation.
- RUBEROID® UltraClad® SBS Membrane is used as a premium modified cap sheet in SBS modified or BUR system flashing.
- Embossed metal surface provides pleasing aesthetics and energy-saving reflectivity.

\* See applicable guarantee for complete coverage and restrictions.

## Applicable Standards

UL approved for use in the construction of Class A, B, or C roof systems

ASTM D6298

## Product Specifications (nominal)

Roll Size	1 square (110.6 gross sq. ft.) (10.27 m <sup>2</sup> )
Roll Length	33.4' (10.1 m)
Roll Width	39.75" (1.0 m)
Approx. Roll Weight	101 lb (45.8 kg)
Product Thickness	0.145" (3.7 mm)