



24 GAUGE CONTINUOUS HOOK STRIP  
SECURED WITH DRILL-TEC™ FASTENERS  
@ 12" O.C.

EVERGUARD® COATED METAL GRAVEL  
STOP WITH HEMMED EDGE

GALVANIZED ANGULAR RING SHANK  
NAIL @ 4" O.C. STAGGERED OR  
DRILL-TEC™ SCREWS 12" O.C.

HEAT WELDED LAP

WOOD NAILER, 5/4" X 4" MIN. SECURED  
TO DECK

EVERGUARD® 8" WIDE MEMBRANE  
FLASHING STRIP

HEAT WELDED LAP

EVERGUARD® FREEDOM MEMBRANE

ENERGYGUARD™ ROOF INSULATION

ROOF DECK/SUBSTRATE

**NOTE:**

1. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES  
(REFER TO DETAIL FD 115).



**GRAVEL STOP COATED METAL ROOF  
EDGE**

DRAWING #  
**202**

SYSTEM  
**FD**

ROOF EDGE SERIES

HEATWELD ONLY

SCALE  
N.T.S.

ISSUE/ REVISION DATE  
3-1-10