

Product Data Sheet

EverGuard<sup>®</sup>  
Sealants

Updated: 8/09



*Your Best and Safest Choice<sup>™</sup> ...  
Quality You Can Trust Since 1886!*

# Product Data Sheet

## EverGuard® Sealants

### Description

GAF EverGuard® single-ply roofing systems include a full line of EverGuard®/GAF sealants.

**Note:** EverGuard®/GAF sealants are specially formulated for specific applications: be sure to use the correct sealant for the application. The following EverGuard®/GAF sealants are available:

Product	Description	Benefit/Application	Units Per Carton	Carton Weight
<b>EverGuard® Water Block</b>	One-part butyl-based high-viscosity sealant	<ul style="list-style-type: none"> <li>• Suitable for sealing between flashing membrane and substrate surface behind exposed termination bars</li> <li>• Suitable for sealing between roofing membrane and drain flanges</li> </ul>	25 10.5 oz. cartridges	13 lbs.
<b>EverGuard® 2-Part Pourable Sealant</b>	100% solids urethane-based two-part sealant	<ul style="list-style-type: none"> <li>• Suitable for filling sealant pans at irregularly-shaped penetrations</li> </ul>	1 kit = 1 gal Part A and 1 pint Part B 2 kits per carton	18 lbs.
<b>EverGuard® TPO &amp; PVC Cut Edge Sealant</b>	Sealant used at any non-factory edge of TPO and PVC membrane	<ul style="list-style-type: none"> <li>• Used to seal non-factory edges (cut edges) as a final step in reinforced membrane installation</li> <li>• PVC Cut Edge with PVC</li> <li>• TPO Cut Edge with TPO</li> </ul>	<ul style="list-style-type: none"> <li>• 12 pints/ctn.</li> <li>• 100 lineal feet per pint @ 1/8" diameter bead.</li> </ul>	12 lbs.

**Storage:**

- Store sealants in original containers on pallets or shelving in a dry area.
- Store sealants in 50-100°F conditioned area away from open flame or other combustion source.
- Do not allow to freeze.