

# TOPCOAT® Liquid-Applied Roofing Systems

## Exterior Metal Wall System

(TOPGN160)

Updated: 7/14



*Quality You Can Trust...From  
North America's Largest Roofing Manufacturer!™*

# EXTERIOR METAL WALL SYSTEM



## Original Application

- Traditional Installations: Exterior metal walls.
- Typical Property: Large low-rise buildings, warehouses, and public buildings.
- Reason for Installation: Waterproof and protect vertical metal surfaces.

## System Advantage

Protection for walls provides superior water resistance, great looks, and the long-lasting protection of an elastomeric membrane.

## Features

- Reflective: ENERGY STAR® qualified reflective product (white only).
- Durable: Adds 32 wet mils of liquid-applied membrane to existing surface.
- Protection: Waterproofs and protects walls; decorative.

## Guarantee/Warranty Eligibility

- Weather Stopper® Integrated System Limited Warranty.\*
- Can be part of the 20-year Diamond Pledge™ NDG Guarantee.\*

## TOPCOAT® System Advantages

- Reflectivity: ENERGY STAR® qualified (white only) high-reflectivity can mean substantial energy savings by reducing interior building temperatures.
- Diamond Pledge™ NDG Roof Guarantee.\*
- Weather Stopper® Integrated System Limited Warranty.\*
- Guarantee and limited warranty backed by GAF, North America's largest roofing materials manufacturer.\*
- High Solids: Liquid-applied membrane with 71 ± 5% solids; average membrane thickness is 18-20 dry mils when applied at 2 gallons per square.
- Performance: Elastomeric properties provide stronger resistance to discoloration and fading while helping to resist blistering, flaking, and peeling.
- Extra Protection: Helps to prevent weather infiltration while providing a breathable membrane.

## Quick Spec

- Step 1) Pressure-wash walls.
- Step 2) Treat all wall penetrations and scuppers with TOPCOAT® Flashing Fabric embedded into TOPCOAT® Flashing Grade.
- Step 3) Treat all horizontal seams with TOPCOAT® Flashing Grade and TOPCOAT® Flashing Fabric.
- Step 4) Spray-apply base coat of TOPCOAT® Membrane at 1 gallon per square.
- Step 5) Spray-apply finish coat of TOPCOAT® Membrane at 1 gallon per square.

**This Quick Spec is meant only as an overview of installation procedures. It is not meant to replace the detailed specification requirements that appear in the Low-Slope / Restoration System Specifications section of this Manual. Be sure to review detailed specification prior to beginning any project.**

\*See limited warranty and guarantee for complete coverage and restrictions. Roof must have positive drainage.

**NOTE:** This quick specification is for water-based products.

