

# EverGuard® EPDM Splice Wash

## Information Sheet



*Quality You Can Trust Since 1886...  
From North America's Largest Roofing Manufacturer™*

# TECHNICAL INFORMATION SHEET

## EVERGUARD® EPDM SPLICE WASH

### DESCRIPTION:

EverGuard EPDM Splice Wash is designed to clean and prepare EverGuard EPDM single-ply membranes to receive adhesives where required by EverGuard EPDM Specifications and Details.

### METHOD OF APPLICATION:

Apply EverGuard EPDM Splice Wash to the splicing area using a clean, white, natural fiber rag. Use a scrubbing motion until the splicing surface is clean of dirt and debris. Additional attention must be given to factory seams and where other excess accumulations of dusting agent occur. Allow the washed surfaces to dry until the solvent's sheen is gone. This is usually between 10-30 minutes and may vary with ambient weather conditions. Membrane is clean when it is uniformly dark gray in color without streaks.

### COVERAGE RATE:

1. Coverage rate of 200-250 square feet per gallon (4.9 - 6.1 sq. m/L) (one side)

### STORAGE:

1. Store in original unopened pails indoors at temperature between 60°F(16°C) and 80°F(26.7°C) away from all sources of direct heat and ignition - this is a flammable liquid.
2. When exposed to lower temperatures, restore to room temperature prior to use.
3. Keep the material out of direct sunlight until ready for immediate use.

### SHELF LIFE:

1. Shelf life of one year can be expected if stored in original unopened pails at temperatures between 60°F (16°C) and 80°F (26.7°C).

This sheet is meant only to highlight EverGuard products and specifications. Information is subject to change without notice.

GAFMC takes responsibility for furnishing quality materials which meet EverGuard EPDM published product specifications. As neither GAFMC itself nor its representatives practice architecture, GAFMC offers no opinion on, and expressly disclaims any responsibility for, the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. GAFMC accepts no liability for any structural failure or resultant damages, and no GAFMC employee or representative is authorized to vary this disclaimer.

## PRODUCT DATA:

<u>Property</u>	<u>Minimum Performance</u>
Solvents:	Aliphatic Hydrocarbon Mixture
Viscosity:	Very thin, free flowing
Weight per Gallon:	6.3 lb/gal (6.75 kg/L) – Nominal
Specific Gravity:	.75 – Nominal
Flash Point:	55° F (12.8° C)
Boiling Point:	247°F (119.4 °C)

### PRECAUTIONARY DATA:

1. Thinning is not allowed.
2. Flammable Liquid. Store and use away from all sources of direct heat and ignition. Keep containers closed when not in use.
3. Use of solvent-resistant Neoprene is required when applying EverGuard EPDM Splice Wash. Do not allow EverGuard EPDM Splice Wash to come in direct contact with skin.
4. Avoid breathing vapors.
5. Refer to Material Safety Data Sheet (MSDS) for additional precautionary data.
6. Do not use as a pre-wash for any EverGuard EPDM Tape products. EverGuard EPDM Primer must be used for EverGuard EPDM Tape products.
7. Refer to the Technical Information Sheet titled "Recommended to Guidelines For Application Of Adhesives To Occupied Buildings".