



GAF Materials Corporation
Material Safety Data Sheet
MSDS # 1059
MSDS Date: October 2013

SECTION 1: PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: TOPCOAT® SB - 900 Flashing Grade
TRADE NAME: N/A
CHEMICAL NAME / SYNONYM: N/A
CHEMICAL FAMILY: N/A
MANUFACTURER: GAF Materials Corporation
ADDRESS: 1361 Alps Road, Wayne, NJ 07470
24-HOUR EMERGENCY PHONE (CHEMTREC): 800 – 424 – 9300
INFORMATION ONLY: 800 – 766 – 3411
PREPARED BY: Corporate EHS
APPROVED BY: Corporate EHS

NFPA Hazard Rating

HMIS Hazard Rating

Health	2	Health	2
Flammable	3	Flammable	3
Reactive	0	Reactive	0
Special Hazards	-	Personal Protection	X

OSHA HAZARDOUS: Yes No

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

CHEMICAL NAME	CAS #	% (BY WT)	OSHA	ACGIH	OTHER
Calcium Carbonate	1317-65-3	28-36	5 mg/m ³ – resp. 15 mg/m ³ – total	3 mg/m ³ – resp. 10 mg/m ³ – total	REL: 5 mg/m ³ – resp., 10 mg/m ³ – total
Xylene	1330-20-7	14-21	100 ppm	100 ppm	REL: 100 ppm

OCCUPATIONAL EXPOSURE LIMITS

CHEMICAL NAME	CAS #	% (BY WT)	OSHA	ACGIH	OTHER
PolyButene	9003-29-6	3-10	NE	NE	NE
Toluene	108-88-3	1-8	200 ppm	20 ppm	REL: 100 ppm
Titanium Dioxide	13463-67-7	1-8	15 mg/m ³ – total	10 mg/m ³ – total	REL: lowest feasible concentration
Ethylbenzene	100-41-4	1-5	100 ppm	100 ppm	REL: 100 ppm
Non-Hazardous Ingredients	N/A	68-76	NE	NE	NE

NE= Not Established

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE OF EXPOSURE: Skin Absorption, Inhalation, and Ingestion

SIGNS & SYMPTOMS OF EXPOSURE

EYES: This material is an eye irritant. Contact with the liquid or exposure to mist or vapor may cause stinging, redness and swelling.

SKIN: This material may cause mild skin irritation. Prolonged contact may cause redness, burning and drying or cracking of the skin. Skin absorption may produce systemic toxicity.

INGESTION: Harmful or fatal if swallowed and/or vomiting occurs. Can enter lungs and cause damage or lung inflammation. Do not induce vomiting.

INHALATION: High concentrations of vapor or mist may cause irritation of the nose and throat and signs of nervous system depression. Can cause headaches, drowsiness, dizziness, and loss of coordination. May affect liver, kidneys, and respiratory system.

ACUTE HEALTH HAZARDS: Excessive exposure can cause pulmonary edema.

CHRONIC HEALTH HAZARDS: Respiratory or lung disorders may be aggravated by exposure to this material.

CARCINOGENICITY: IARC has determined that occupational exposure to Titanium Dioxide and Ethylbenzene are possibly carcinogenic to humans (Group 2B). IARC concluded lung tumors were observed in rats following high dose exposure by inhalation and in female rats exposed by intra-tracheal instillation. Other studies have shown no

tumors in rats following inhalation exposure and no tumors in mice or rats following oral exposure.

SECTION 4: FIRST AID MEASURES

FIRST AID PROCEDURES

EYES: Flush eyes with water for 15 minutes. If irritation or reddening persists, call physician.

SKIN: Remove contaminated clothes. Wash exposed areas with soap and water. If redness or swelling develops, seek medical attention.

INHALATION: Move the individual to an area with fresh air or provide oxygen immediately, call physician.

INGESTION: If swallowed, contact physician immediately. Do not induce vomiting. This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: N/A

SECTION 5: FIRE FIGHTING PROCEDURES

SUITABLE EXTINGUISHING MEDIA: Water, Fog, CO₂, and foam.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide and carbon monoxide

RECOMMENDED FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE & EXPLOSION HAZARDS: Material is flammable and may be ignited by flames, sparks, heat or other sources of ignition.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Dam up area to prevent spreading of material. Provide ventilation. Extinguish all open flames, electrical sparks, or static electricity. Dry up the compound using an absorbent material.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE:

Store in a well ventilated area at temperatures between 50 - 80° F. Avoid open flames or electrical spark sources. Container should be grounded when pouring.

OTHER PRECAUTIONS:

The container is hazardous when empty. Partially full or emptied container may contain explosive vapors. Do not cut, weld or solder on or near the container. Do not reuse "empty" container without commercial cleaning or reconditioning.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS / VENTILATION:

Provide sufficient mechanical ventilation to maintain exposure below exposure limits.

RESPIRATORY PROTECTION:

Use NIOSH approved organic vapor cartridge type respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respiratory use (29 CFR 1910.134).

EYE PROTECTION:

Safety goggles or safety glasses with side shields.

SKIN PROTECTION:

Wear appropriate impermeable gloves to prevent skin contact.

OTHER PROTECTIVE EQUIPMENT:

N/A

WORK HYGIENIC PRACTICES:

Wash exposed skin prior to eating, drinking, or smoking and at the end of each shift.

EXPOSURE GUIDELINES:

N/A

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR:	Heavy white paste with paint thinner odor.		
FLASH POINT:	79° F	LOWER EXPLOSIVE LIMIT:	1.1
METHOD USED:	TCC	UPPER EXPLOSIVE LIMIT:	6.6
EVAPORATION RATE:	0.8	BOILING POINT:	280° F
pH (undiluted product):	No Data	MELTING POINT:	No Data
SOLUBILITY IN WATER:	Insoluble	SPECIFIC GRAVITY:	1.24
VAPOR DENSITY:	3.7	PERCENT VOLATILE:	No Data
VAPOR PRESSURE:	6.6 mmHg @ 22°C	MOLECULAR WEIGHT:	No Data
VOC WITH WATER (LBS/GAL):	No Data	WITHOUT WATER (LBS/GAL):	No Data

--	--	--	--

SECTION 10: STABILITY AND REACTIVITY

THERMAL STABILITY: **STABLE** X **UNSTABLE**

CONDITIONS TO AVOID (STABILITY): N/A

INCOMPATIBILITY (MATERIAL TO AVOID): Avoid strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon monoxide or carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: No information available.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No information available.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: This product, as supplied, is regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. If discarded in its purchased form, this product is a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or residue of the product remains classified a hazardous waste as per 40 CFR 261, Subpart C. State or local regulations may also apply if they differ from the federal regulation.

RCRA HAZARD CLASS: D001, Ignitable Hazardous Waste

SECTION 14: TRANSPORTATION INFORMATION

U.S. DOT TRANSPORTATION

PROPER SHIPPING NAME: Coating Solution
HAZARD CLASS: 3
ID NUMBER: UN 1139
PACKING GROUP: III
LABEL STATEMENT: N/A
OTHER: N/A

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA: This product and its components are listed on the TSCA 8(b) inventory.

CERCLA: None

SARA

311/312 HAZARD CATEGORIES: Chronic health hazard.

313 REPORTABLE INGREDIENTS: Xylene 1330-20-7 14-21%
Toluene 108-88-3 1-8%
Ethylbenzene 100-41-4 1-5%
Titanium Dioxide 13463-67-7 1-8%
Calcium Carbonate 1317-65-3 28-36%

CALIFORNIA PROPOSITION 65: This product possibly contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm. Cancer: Cadmium Oxide, Lead Oxide, Formaldehyde, 2-Chloro-1,3-Butadiene, Quartz / Sand, Benzene, Ethyl Benzene. Reproductive: Toluene, Benzene, Lead Oxide, Cadmium Oxide.

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

Chemical Name	CAS #	CA	MA	MN	NJ	PA	RI
Calcium Carbonate	1317-65-3	No	No	No	No	Yes	No
Xylene	1330-20-7	Yes	Yes	Yes	Yes	No	Yes
PolyButene	9003-29-6	No	No	No	No	No	No
Toluene	108-88-3	Yes	Yes	Yes	Yes	No	Yes

Titanium Dioxide	13463-67-7	No	No	No	Yes	Yes	Yes
Ethylbenzene	100-41-4	Yes	No	Yes	Yes	No	Yes

SECTION 16: OTHER INFORMATION

ADDITIONAL COMMENTS: N/A

DATE OF PREVIOUS MSDS: January 2011

CHANGES SINCE PREVIOUS MSDS: Added IARC information.

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.