

TOPCOAT® Liquid-Applied Roofing Systems

TOPCOAT® Recommended Equipment

(TOPGN160)

Updated: 7/14



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*

TOPCOAT® RECOMMENDED EQUIPMENT

The GAF Technical Services Department recommends that the following tools and equipment be on site and available for the preparation and installation of TOPCOAT® Repair and/or Maintenance Systems:

- Adequate water source for pressure washing and clean-up
- Adequate source of electrical power
- Wire brush for removing rust
- Utility knives
- Metal snips
- Reciprocating saw
- Drill or screw gun for tightening fasteners (or T-bar with hex fitting to match fastener size)
- Polyurethane foam or closed-cell foam strips to fill excessive voids in ridge vents, duct work, etc., before TOPCOAT® Flashing and TOPCOAT® Flashing Fabric are applied
- Thick-bristle brushes (2"- 4") to apply various TOPCOAT® products
- Low-nap rollers to apply various TOPCOAT® products
- Caulking guns for application of TOPCOAT® Flashing Grade in cartridges
- Self-drilling stitching screws to properly secure seams, ridge cap, and penetrations
- Pressure washer with minimum working pressure of 3,000 psi equipped with roto-spray tip
- Airless spray system with a minimum working pressure of 2,000 psi/3,000 psi (remove filters) and reversible spray tips for TOPCOAT® product application
- Leister Heat Gun or soldering pencil with pencil tip to make holes in TOPCOAT® Flashing Fabric around fasteners that are present when three-coursing
- Rags

For application questions, please contact GAF Technical Services at 1-800-766-3411.

