

# EverGuard® Adhesives and Primers

## Information Sheet



*Quality You Can Trust Since 1886...  
From North America's Largest Roofing Manufacturer™*

# Product Data Sheet

## EverGuard®

### Adhesives & Primers

#### Description

EverGuard® single-ply roofing systems include a full line of EverGuard/GAF® adhesives.

**Note:** EverGuard/GAF adhesives are specially formulated for use with specific EverGuard membranes; use the correct adhesive for the application. The following EverGuard/GAF adhesives are available:

Product	Description	Benefit/Application	Quantity/Size	Weight
<b>EverGuard PVC Bonding Adhesive</b>	Solvent-based rubberized adhesive for use with PVC-based membranes	<ul style="list-style-type: none"> <li>Two-surface contact adhesive applied to both underside of membrane and substrate surface</li> <li>Suitable for roofing and flashing membranes, including fleece-backed membranes.</li> <li>Compatible with isocyanurate and fiberboard insulations, and fiber glass-faced gypsum panels</li> <li>Compatible with concrete, masonry, metal and wood flashing substrates</li> </ul>	5 gallon pail	36 lbs.
<b>EverGuard TPO Bonding Adhesive</b>	Solvent-based rubberized adhesive for use with TPO-based membranes	<ul style="list-style-type: none"> <li>Two-surface contact adhesive applied to both underside of membrane and substrate surface</li> <li>Suitable for roofing and flashing membranes including fleece-backed membranes.</li> <li>Compatible with isocyanurate and fiberboard insulations, and fiber glass-faced gypsum panels</li> <li>Compatible with concrete, masonry, metal and wood flashing substrates</li> </ul>	5 gallon pail	36 lbs.
<b>EverGuard H<sub>2</sub>O Bonding Adhesive</b>	Water-based rubberized adhesive for PVC-based and TPO-based membranes	<ul style="list-style-type: none"> <li>Two-surface contact adhesive applied to both underside of membrane and substrate surface</li> <li>Suitable for roofing and flashing membranes, including fleece-back membranes</li> <li>Compatible with isocyanurate and fiberboard, insulations, and fiber glass-faced gypsum panels</li> <li>Compatible with concrete, masonry, metal and wood flashing substrates</li> </ul>	5 gallon pail	38 lbs.
<b>EverGuard TPO Primer</b>	Standard solvent-based primer	<ul style="list-style-type: none"> <li>Solvent based primer for galvanized metal edges cover tape</li> <li>Cleans and prepares TPO membrane and galvanized metal edges prior to installation of EverGuard TPO Cover Tape</li> <li>Apply Primer using Scotch Brite Pad or equivalent.</li> <li>Application rate approximately 560 lineal feet per gallon.</li> </ul>	1 gallon can 5 gallon pail	8 lbs. 40 lbs.
<b>EverGuard TPO Seam Cleaner</b>	Solvent-based seam cleaner	<ul style="list-style-type: none"> <li>Use to clean exposed or contaminated seam prior to heat welding.</li> <li>Use with self-adhering membrane prior to adhering the lap.</li> </ul>	1 gallon can	7 lbs.
<b>GAF Asphalt Primer</b>	General purpose solvent-based asphalt primer	<ul style="list-style-type: none"> <li>Meets ASTM D-41</li> <li>Asphalt primer required prior to application of roofing asphalt</li> <li>Seals and conditions surface of old smooth and mineral-surfaced built-up roofs, structural, cellular and gypsum concrete decks, and masonry wall surfaces</li> </ul>	5 gallon	37 lbs.

Note: Store adhesives and primers in original pails on pallets or shelving in a dry area. 50-100°F conditioned area away from open flame or other. Mass and dimensions stated as nominal unless otherwise indicated.