

# EverGuard® TPO Low VOC TPO Bonding Adhesive Sell Sheet

Updated: 1/12



*Quality You Can Trust...From  
North America's Largest Roofing Manufacturer!™*

[www.gaf.com](http://www.gaf.com)



# EverGuard® TPO

SINGLE-PLY ROOFING SYSTEMS

## Description

EverGuard® Low VOC TPO Bonding Adhesive is a contact-type bonding adhesive specially designed for bonding TPO single-ply roofing membranes and flashings to various roofing substrates. EverGuard® Low VOC TPO Bonding Adhesive contains less than 250 grams per liter of Volatile Organic Content (VOC) and has been formulated using a blend of VOC-exempt and non-exempt solvents to be in compliance with air quality regulations for single-ply roofing adhesives.

## Features and Benefits

- Low VOC—<250 g/L
- High coverage—up to 120 sq. ft. per gallon of bonded membrane
- Fast-drying solvent system
- Easy application using roller or brush
- High initial tack

## Physical Properties

**Base:** Synthetic polymer  
**Solvent:** VOC-compliant blend  
**Flash Point:** -9.4°F (-23°C)  
**Weight/Gallon:** 7.97 lbs  
**Color:** Yellow  
**Viscosity:** 1,200 – 1,700 cps  
**Coverage:** 100 – 120 sq. ft./gallon

**Total Solids:** 38% +/- 1%  
**VOC:** 247 grams/liter  
**Shelf Life:** 1 year, unopened  
**Open Time:** Up to 60 minutes  
**Dry Time:** 5 – 15 minutes  
**Application:** Roller, brush, or spray

**Storage:** Recommended storage temperature range 40°F–90°F (4°C–32.2°C). Shelf life approximately 1 year. Storage for continued periods outside this temperature range may shorten shelf life.

**Installation Temperature:** Minimum application temperature of bonding adhesive is 40°F (4°C) and rising.



## Low VOC TPO Bonding Adhesive

## Ordering Information

**Item Number:** 7784  
**Packaging:** 5 gallon pails  
**Weight:** 48 lbs/pail  
**Shipping:** 45 pails per pallet

Low VOC TPO Bonding Adhesive

Quality You Can Trust...From North America's Largest Roofing Manufacturer!™