

TOPCOAT[®] FLEXSEAL CAULK GRADE

Material Safety Data Sheet

MSDS #2128

Updated: 3/2010



*Your Best and Safest Choice[™] ...
Quality You Can Trust Since 1886!*



GAF Materials Corporation
Material Safety Data Sheet
MSDS # 2128
MSDS Date: March 2010

SECTION 1: PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: TOPCOAT® FlexSeal Caulk Grade
TRADE NAME: N/A
CHEMICAL NAME / SYNONYM: N/A
CHEMICAL FAMILY: N/A
MANUFACTURER: GAF Materials Corporation
ADDRESS: 1361 Alps Road, Wayne, NJ 07470
24-HOUR EMERGENCY PHONE (CHEMTREC): 800 – 424 – 9300
INFORMATION ONLY: 800 – 766 – 3411
PREPARED BY: Corporate EHS
APPROVED BY: Corporate EHS

NFPA Hazard Rating

HMIS Hazard Rating

Health
Flammable
Reactive
Special Hazards

2
3
0
-

Health
Flammable
Reactive
Personal Protection

2
3
0
X

OSHA HAZARDOUS: Yes X

No

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

CHEMICAL NAME	CAS #	% (BY WT)	OSHA	ACGIH	OTHER
Calcium Carbonate	1317-65-3	30 – 40	5 mg/m ³ – resp. 15 mg/m ³ – total	3 mg/m ³ – resp. 10 mg/m ³ – total	REL: 5 mg/m ³ – resp. 10 mg/m ³ – total
Xylene	1330-20-7	10 – 20	100 ppm	100 ppm 125 ppm STEL	REL: 100 ppm 125 ppm STEL

OCCUPATIONAL EXPOSURE LIMITS

CHEMICAL NAME	CAS #	% (BY WT)	OSHA	ACGIH	OTHER
Polybutene	9003-29-6	2 – 10	NE	NE	NE
Ethylbenzene	100-41-4	2 – 10	100 ppm	100 ppm 125 ppm STEL	REL: 100 ppm 125 ppm STEL
Toluene	108-88-3	2 – 10	200 ppm 300 ppm ceiling	20 ppm	REL: 100 ppm 150 ppm STEL
Styrene- alphamethylstyrene resin	9011-11-4	2 – 10	NE	NE	NE
Crystalline Silica	14808-60-7	0 – 1	10 mg/m ³ / (% SiO ₂ + 2) – resp.	0.025 mg/m ³	REL: 0.05 mg/m ³ – resp.
Non-hazardous ingredients	n/a	20 – 30	NE	NE	NE

NE = Not Established

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE OF EXPOSURE: Eye contact, Skin contact, Inhalation

SIGNS & SYMPTOMS OF EXPOSURE

EYES: This material is an eye irritant. Contact with the liquid or exposure to mist or vapor may cause stinging, redness and swelling.

SKIN: This material may cause mild skin irritation. Prolonged contact may cause redness, burning and drying or cracking of the skin. Skin absorption may produce systemic toxicity.

INGESTION: Harmful or fatal if swallowed and/or vomiting occurs. Can enter lungs and cause damage. This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

INHALATION: High concentrations of vapor or mist may cause irritation of the nose and throat and signs of nervous system depression. Can cause headaches, drowsiness, dizziness, and loss of coordination. May affect liver, kidneys and respiratory system.

ACUTE HEALTH HAZARDS: See above.

CHRONIC HEALTH HAZARDS: Respiratory or lung disorders may be aggravated by exposure to this material.

CARCINOGENICITY:

Ethyl Benzene is classified as a 2B carcinogen (possibly carcinogenic to humans) by the International Agency for Research on Cancer (IARC).

Titanium Dioxide is classified as a 2B carcinogen (possibly carcinogenic to humans) by the International Agency for Research on Cancer (IARC).

The International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) have determined that there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite. In addition, IARC has determined that there is sufficient evidence for the carcinogenicity of quartz and cristobalite in experimental animals. Among individuals with silicosis, lung cancer occurs more frequently in those who smoke.

SECTION 4: FIRST AID MEASURES

FIRST AID PROCEDURES

EYES:	Flush eyes immediately with water for 15 minutes. Call a physician.
SKIN:	Remove contaminated clothes. Wash exposed areas with soap and water. If redness or swelling develops, seek medical assistance.
INHALATION:	Remove to fresh air. If breathing has stopped, give artificial respiration. Call a physician.
INGESTION:	Do not induce vomiting. Contact physician immediately.
NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:	None.

SECTION 5: FIRE FIGHTING PROCEDURES

SUITABLE EXTINGUISHING MEDIA:	Water, fog, CO ₂ , and foam.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide and carbon monoxide.
RECOMMENDED FIRE FIGHTING PROCEDURES:	Self contained breathing apparatus recommended.
UNUSUAL FIRE & EXPLOSION HAZARDS:	Material is flammable and may be ignited by flames, sparks, heat or other sources of ignition.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Dam up area to prevent spreading of material. Use absorbent material to dry up liquid. Shut off all sources of open flames, electrical sparks, or static electricity.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Store in a well ventilated area, 50 – 80 °F.

OTHER PRECAUTIONS: Avoid open flames, electrical sparks or static electricity.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS / VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure limits.

RESPIRATORY PROTECTION: Use NIOSH-approved respirator.

EYE PROTECTION: Safety goggles or safety glasses with side shields.

SKIN PROTECTION: Wear appropriate impermeable gloves and protective clothing as necessary to prevent skin contact.

OTHER PROTECTIVE EQUIPMENT: N/A

WORK HYGIENIC PRACTICES: Wash exposed skin prior to eating, drinking, or smoking and at the end of each shift.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR:	Heavy white paste with paint thinner odor.		
FLASH POINT:	79 °F	LOWER EXPLOSIVE LIMIT:	1.1%
METHOD USED:	TCC	UPPER EXPLOSIVE LIMIT:	6.6%
EVAPORATION RATE:	0.8	BOILING POINT:	280 °F
pH (undiluted product):	No data	MELTING POINT:	No data
SOLUBILITY IN WATER:	No data	SPECIFIC GRAVITY:	1.24
VAPOR DENSITY:	3.7	PERCENT VOLATILE:	No data

VAPOR PRESSURE:	6.6 @ 20 °C	MOLECULAR WEIGHT:	No data
VOC WITH WATER (LBS/GAL):	No data	WITHOUT WATER (LBS/GAL):	No data

SECTION 10: STABILITY AND REACTIVITY

THERMAL STABILITY: STABLE UNSTABLE

CONDITIONS TO AVOID (STABILITY): None known.

INCOMPATIBILITY (MATERIAL TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon dioxide or carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: No information available.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No information available.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: This product, as supplied, is regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. If discarded in its purchased form, this product is a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or residue of the product remains classified a hazardous waste as per 40 CFR 261, Subpart C. State or local regulations may also apply if they differ from the federal regulation.

RCRA HAZARD CLASS: D001, Ignitable Hazardous Waste

SECTION 14: TRANSPORTATION INFORMATION**U.S. DOT TRANSPORTATION**

PROPER SHIPPING NAME: Coating Solution
HAZARD CLASS: 3
ID NUMBER: UN1139
PACKING GROUP: III
LABEL STATEMENT: N/A
OTHER: N/A

SECTION 15: REGULATORY INFORMATION**U.S. FEDERAL REGULATIONS**

TSCA: This product and its components are listed on the TSCA 8(b) inventory.

CERCLA: CERCLA Hazardous Substances (40 CFR 302)

Reportable Quantity – Components

Xylene, 1330-20-7, 1000 lbs.
Toluene: 108-88-3, 1000 lbs.
Ethyl Benzene: 100-41-4, 1000 lbs.

SARA

311/312 HAZARD CATEGORIES: Acute Health Hazard, Chronic Health Hazard, Fire Hazard

313 REPORTABLE INGREDIENTS: Xylene 1330-20-7, 10 – 20%
Toluene 108-88-3, 2 – 10%
Ethyl Benzene 100-41-4, 2 – 10%

CALIFORNIA PROPOSITION 65: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

Chemical Name	CAS #	CA	MA	MN	NJ	PA	RI
Calcium Carbonate	1317-65-3	No	Yes	Yes	No	Yes	Yes
Xylene	1330-20-7	Yes	Yes	Yes	Yes	Yes	Yes

Polybutene	9003-29-6	No	No	No	No	No	No
Ethylbenzene	100-41-4	Yes	Yes	Yes	Yes	Yes	Yes
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes	Yes
Styrene-alpha-methylstyrene resin	9011-11-4	No	No	No	No	No	No
Titanium Dioxide	13463-67-7	No	No	Yes	Yes	Yes	Yes
Crystalline Silica	14808-60-7	Yes	Yes	Yes	Yes	Yes	Yes

SECTION 16: OTHER INFORMATION

ADDITIONAL COMMENTS: None

DATE OF PREVIOUS MSDS: N/A

CHANGES SINCE PREVIOUS MSDS: New MSDS

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.