

TopCoat® Liquid Fabric Flashing Grade

Information Sheet

Updated: 1/07



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*



LIQUID FABRIC FLASHING GRADE

Description

TOPCOAT® Liquid Fabric Flashing Grade is a light gray, water-based, flexible liquid fabric seam sealer that does not require reinforcing fabric on properly fastened horizontal seams of metal roofs – reduces horizontal seam labor up to 50%. This product can be used to seal properly fastened horizontal seams on metal roofs *without* the use of TOPESTER Fabric when horizontal seams are properly secured as per product application specifications.

Uses

Liquid Fabric Flashing Grade is designed for use on metal, wood and concrete to provide a strong flexible seal that will not become brittle. Do not apply at temperatures below 42°F. Substrate temperatures must be below 120°F when applying product.

Advantages

- Strong; forms a flexible seal that will not become brittle
- Flexible; will expand and contract with metal roof

- A time saver! Reduces horizontal seam labor up to 50%; up to 10% on the whole job
- Ideal for properly fastened horizontal seams on metal roofs
- Warranties available for up to 10 years*
- Guarantees available for up to 20 years*
- Available in 5-gallon pails and 55-gallon containers

For application questions, please contact GAFMC Contractor Services at 1-800-766-3411.

Applicable Standards

ASTM D-412, ASTM G-21, ASTM D-21-96, ASTM D-1475, ASTM E-1644, FTMS141.6271

Note: Repair leaks promptly to avoid adverse effects, including mold growth.

*See warranties and guarantees for complete coverage and restrictions.

TOPCOAT® LIQUID FABRIC FLASHING GRADE TECHNICAL DATA

Application Rate:	5 gallons/125 lineal ft. of seam (6" wide)
Application Method:	Brush or airless sprayer
Application Temp (air, surface):	42° - 120°F
Drying Time (75°F, 50% RH):	Approximately 24 hours
Recommended Wet Mil Thickness:	105 wet mils
Recommended Dry Mil Thickness:	60 dry mils
Total Solids (by weight):	71.7% ± 2%
Total Solids (by volume):	55% ± 2%
Specific Gravity:	1.35 ± 0.1
Weight per Gallon:	11.3 ± 0.5 lbs
Elongation:	700%
Viscosity (75°F):	130,000 ± 15,000 cps
Storage:	Store in well-ventilated area at 50°F to 80°F; protect from freezing
Shelf Life:	1 Year
Clean-up:	Water before curing



For further information, contact GAF Contractor Services at: 1-800-766-3411 or visit www.gaf.com
©2007 GAF Materials Corporation 1/07