

TopCoat® MP-300 Rust Inhibiting Primer

Information Sheet

Updated: 1/04



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*



*“Don’t Repair Or Replace It...
Restore It And Save”*

MP-300

RUST INHIBITING PRIMER



Designed For Use On:
• Metal



NO SEAMS. NO LEAKS. NO PROBLEMS.

A water-based industrial primer/rust inhibitor applied to areas of rust before TOPCOAT® Flashing Grade or TOPCOAT® Elastomeric Roofing Membrane.

TOPCOAT® MP-300 Rust Inhibitor is:

- Used to inhibit further rust and provide added protection
- Light blue in color to ensure proper application
- Ideal for use in preventing rust from bleeding through TOPCOAT® Elastomeric Roofing Membrane
- Non-flammable, VOC compliant and easy to clean up
- Available in 5 pails, 55 gallon containers and bulk totes
- Warranties available for up to 10 years*
- Guarantees available for up to 20 years*

Recommended uses:

Apply to areas of rust on sound metal roof panels.

*See warranties and guarantees for complete coverage and restrictions.

**Quality You Can Trust Since 1886...from
North America’s Largest Roofing Manufacturer**



PRODUCT DATA

MP-300 RUST INHIBITING PRIMER

Light blue-pigmented, water-based rust inhibitor that must be applied to any areas of rust before TOPCOAT® Flashing Grade or TOPCOAT® Elastomeric Roofing Membrane can be applied. Do not apply at temperatures below 42°F. Substrate temperatures must be below 120°F when applying this product.

Application Rate:	1 gallon/100 sq. ft.
Application Method:	Airless sprayer or brush
Application Temperature (air, surface):	42° - 120°F
Drying Time (75°F, 50% RH):	Approximately 2 hours
Wet Mil Thickness:	16 wet mils
Dry Mil Thickness:	6 dry mils
Total Solids (by weight):	50% +/- 1%
Total Solids (by volume):	40% +/- 2%
Specific Gravity:	1.19 +/- 0.1
Weight per Gallon:	9.9 +/- 0.5 lbs
Viscosity (75°F):	5,000 +/- 1,000 cps
Clean-up:	Water before curing
ASTM B-117, ASTM C-794, ASTM D-21-96, ASTM D-1475, ASTM E-1644	

NOTE: Repair leaks promptly to avoid adverse effects including mold growth.



Call for more information and a **FREE** brochure and video.

1-800-ROOF-411

www.gaf.com



©2004 GAF Materials Corporation 1/04



TOPLA104