

TopCoat® Sky-Lite (WB)

Information Sheet

Updated: 6/05



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*



SKY-LITE (WB)

Description

TOPCOAT® Sky-Lite is a clear, water-based synthetic rubber sealer designed to protect and waterproof porous, deteriorated fiberglass reinforced skylight panels, in addition to weathered plastic skylights. Water-based skylight is a low odor, low VOC liquid that forms a tough protective layer that penetrates and seals aged fiberglass reinforced plastic skylight panels.

Uses

Sky-Lite is specially designed to seal and rebind fiberglass mat or fiber used in the construction of skylight panels in addition to weathered plastic skylights. Sky-Lite protects and reconditions translucent skylight panels found on roofs and walls. Do Not use to repair cracked or broken skylight panels. Do not apply at temperatures below 42°F. Substrate temperatures must be below 120°F when applying product.

Advantages

- Helps to seal out water and prevents leaking of porous skylight perimeters
- Seals and binds reinforcing fibers and extends the life of the skylight panels
- Reconditions leaky panels
- Assists in the restoration of original skylight clarity
- Water-based, environmentally friendly and safe
- Non-flammable, VOC compliant and easy to clean up
- Warranty available for up to 10 years*
- Available in 5-gallon pails

For application questions, please contact GAFMC Contractor Services at 1-800-766-3411.

Applicable Standards

ASTM D-21-96, ASTM D-1475, ASTM E-1644

Note: Repair leaks promptly to avoid adverse effects, including mold growth.

*See warranties for complete coverage and restrictions.

TOPCOAT® SKY-LITE TECHNICAL DATA

Application Rate:	1 gallon/100 sq.ft. per coat
Application Method:	Roller or brush
Application Temp (air, surface):	42° - 120°F
Drying Time (75°F, 50% RH):	Approximately 1 hour per coat
Wet Mil Thickness:	(1.0 Gallon/100SF) - 16 wet mils
Dry Mil Thickness:	(1.0 Gallon/100SF) - 6 dry mils
Total Solids (by weight):	37.5% ± 2%
Total Solids (by volume):	35% ± 2%
Specific Gravity:	1.25 ± 0.1
Weight per Gallon:	8.54 ± 0.5 lbs
Viscosity (75°F):	1,100 ± 300 cps
Storage:	Store in well-ventilated area at 50°F to 80°F; protect from freezing
Shelf Life:	1 Year
Clean-up:	Water before curing



For further information, contact
GAF Contractors Services at:
1-800-766-3411 or visit www.gaf.com
©2005 GAF Materials Corporation 06/05