

StormSafe™ Anchor Sheet

Data Sheet

Updated: 1/10



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*



STORMSAFE™ ANCHOR SHEET



Description

StormSafe™ Anchor Sheet for self-adhered membranes is a tough, non-breathable synthetic anchor sheet designed and manufactured to meet industry and code requirements for self-adhered low slope roofing applications.

It is a polypropylene woven fabric coated on both sides with polypropylene. StormSafe Anchor Sheet is designed for use as an anchor sheet for Liberty™ (Modified Bitumen) and Freedom™ TPO self-adhered roof systems.

StormSafe Anchor Sheet's woven fabric creates a tough, durable reinforcement and its polypropylene coating makes it suitable for many applications. StormSafe Anchor Sheet is alkaline resistant, making it suitable for use over lightweight insulating concrete systems. The tough woven fabric makes it extremely tear resistant. In addition, the polypropylene coating ensures a good bond with both the butyl adhesive of Freedom™ membranes and the SBS modified adhesive of Liberty™ SA Base/Ply and Liberty Cap membranes.

Uses

StormSafe Anchor Sheet should be applied with the beige color on top (weather side) and white color coating towards the deck side. Suitable substrates include: plywood, OSB, acceptable

Uses (Continued)

EnergyGuard™ Insulations, and lightweight insulating concrete. The product is designed to be installed mechanically over approved roofing substrates using acceptable fasteners that include galvanized nails with 1-inch integral heads or Drill•Tec™ fasteners and plates in accordance with applicable specifications. Prior to installing any self-adhering membrane, StormSafe Anchor Sheet must be clean and dry. Use care walking on the sheet when it is wet as it may be slippery.

Advantages

- System guarantees are available for up to 20 years.
- Lightweight: Adds less than 1.3 lbs per sq to the system
- Durable: Woven fabric provides superior tear strength and excellent dimensional stability

Applicable Standards

- Slip Sheet for Roofing Systems AS TO EXTERNAL FIRE EXPOSURE
- State of Florida Product Approval
- See GAFMC Applications and Specification Manual or UL Directory for specific approval

Products Specifications (nominal)

Roll Size	24 squares (2400 gross sq.ft.) (222.97m ²)
Roll Length	600' (182.9m)
Roll Width	48" (1.2m)
Approx. Roll Weight	67.9 lbs (30.8 kg)