



NOTE:

1. THE FOLLOWING APPLIES FOR MA SYSTEMS ONLY: FOR INSULATION THICKNESSES GREATER THAN 8", CONTACT GAF CONTRACTOR SERVICES FOR ALTERNATE ATTACHMENT REQUIREMENTS. THESE METHODS MAY INCLUDE THE USE OF A HARD BOARD COVERING THE ASSEMBLY.
2. EVERGUARD[®] ADHESIVE/ HOT ASHALT REQUIRED FOR FA SYSTEMS.
3. DRILL-TEC[™] PLATES & SCREWS 6" O.C. REQ'D FOR BA SYSTEMS.
4. ANYTHING 2:12 OR GREATER NEEDS TO BE FASTENED AT ANGLE CHANGE.
5. APPLY EVERGUARD[®] TPO AND PVC CUT EDGE SEALANT TO ALL CUT REINFORCED TPO AND PVC EDGES (REFER TO DETAIL MA/FA/BA 115).

 <small>WWW.GAF.COM</small> 1361 Alps Rd. Wayne, NJ 07470	 <small>SINGLE-PLY ROOFING SYSTEMS</small>	<h2>CHANGE OF PLANE DETAIL</h2>	DRAWING #	SYSTEM
			112	MA/FA/BA
FIELD OF ROOF SERIES			SCALE	ISSUE/ REVISION DATE
			N.T.S.	7-01-11