




- NAIL 12" O.C.
- 24 GA. CONTINUOUS CLIP FASTENED 12" O.C. WITH DRILL-TEC™ FASTENERS
- EVERGUARD® COATED METAL
- GALV. ANGULAR RING SHANK NAIL 4" O.C. STAGGERED OR DRILL-TEC™ SCREWS 12" O.C.
- HEAT WELDED LAP
- 6" COVER STRIP
- HEAT WELDED LAP
- REINFORCED EVERGUARD® MEMBRANE
- EVERGUARD® BONDING ADHESIVE (OPTIONAL)
- DRILL-TEC™ PLATES & SCREWS 12" O.C.
- HEAT WELDED LAP
- REINFORCED EVERGUARD® MEMBRANE
- ENERGYGUARD™ ROOF INSULATION
- ROOF DECK/SUBSTRATE
- WOOD NAILER, 5/4" X 4" MIN. WIDE SECURED TO DECK

NOTE:

1. THE FOLLOWING APPLIES FOR MA SYSTEMS ONLY: FOR INSULATION THICKNESSES GREATER THAN 8", CONTACT GAF CONTRACTOR SERVICES FOR ALTERNATE ATTACHMENT REQUIREMENTS. THESE METHODS MAY INCLUDE THE USE OF A HARD BOARD COVERING THE ASSEMBLY.
2. PLATES AND SCREWS 6" O.C. REQ'D FOR BA SYSTEMS.
3. APPLY EVERGUARD® TPO AND PVC CUT EDGE SEALANT TO ALL CUT REINFORCED TPO AND PVC EDGES (REFER TO DETAIL MA/FA/BA 115).

ALTERNATE BASE REFER TO 307



 GAF MATERIALS CORPORATION www.gaf.com	 SINGLE-PLY ROOFING SYSTEMS	WALL FLASHING WITH COATED METAL EDGE DETAIL	DRAWING #	SYSTEM
			304	MA/FA/BA
PARAPET WALL & CURB SERIES			SCALE	ISSUE/REVISION DATE
			N.T.S.	6-01-10