

EverGuard™ TPO Accessories

Information Sheet

Updated: 1/09



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*

Product Data Sheet EverGuard® TPO Accessories

Description

The GAF Everguard® TPO single-ply roofing system includes an extensive line of EverGuard TPO flashing accessories for use with EverGuard TPO roofing systems. EverGuard flashing accessories are heat welded to the EverGuard roofing membrane. They are easy to install and provide secure protection from roof edge to parapet to penetration to wall. The following EverGuard TPO flashing accessories are available in standard colors of white, gray and tan unless otherwise noted.

Product	Description	Benefit/Application	Quantity/Size	Weight
Preformed Vent Boots	<ul style="list-style-type: none"> 75 mil molded membrane 	<ul style="list-style-type: none"> One standard size accommodates most common pipes and conduits Supplied with stainless steel clamping rings 	<ul style="list-style-type: none"> Fits 1" - 6" diameter pipes 6 Vent Boots per carton 	9 lbs/carton
Preformed Corners	<ul style="list-style-type: none"> 60 mil thick molded membrane 	<ul style="list-style-type: none"> Universal style corner accommodates both inside and outside corners of base and curb flashings 	<ul style="list-style-type: none"> 4" x 4" with 6" flange 20 Corners per carton 	6 lbs/carton
UN-55 Detailing Membrane	<ul style="list-style-type: none"> 55 mil thick unreinforced membrane White, Tan, Gray, Regal Red, Regal Blue, Hartford Green (Energy Tan in the West) 	<ul style="list-style-type: none"> Alternative flashing/reinforcement material for penetrations and corners Required wherever preformed vent boots cannot be used 	<ul style="list-style-type: none"> 24" x 50' roll 	28 lbs/roll
TPO 45 mil Utility Flashing Strip	<ul style="list-style-type: none"> 45 mil thick reinforced membrane White, Tan, Gray, Regal Red, Regal Blue, Hartford Green (Energy Tan in the West) 	<ul style="list-style-type: none"> Use for stripping in coated metal flanges 	<ul style="list-style-type: none"> 8" x 100' roll 	18 lbs/roll
Coated Metal Sheets	<ul style="list-style-type: none"> 24 gauge steel with a 25 mil thick membrane film White, Tan, Gray, Regal Red, Regal Blue, Hartford Green (Energy Tan in the West) 	<ul style="list-style-type: none"> TPO membrane is laminated to galvanized sheet metal Cuts and forms like standard sheet metal Field and flashing TPO membrane heat welds directly to coated metal For metal gravel stop and drip edges, metal base and curb flashing, sealant pans and scupper sleeves 	<ul style="list-style-type: none"> 4' x 10' sheets 10 or 30 sheets per pallet 	47 lbs/sheet
UN-55 T-Joint Cover Patches	<ul style="list-style-type: none"> 55 mil thick unreinforced membrane 	<ul style="list-style-type: none"> Conforming membrane seal for use over T-Joints in 60 and 80 mil membrane applications 	<ul style="list-style-type: none"> 100 patches per box 	9 lbs
Cut Edge Sealant	<ul style="list-style-type: none"> Solvent-based liquid sealant Clear 	<ul style="list-style-type: none"> Sealant provided in squeeze bottle for use along all cut reinforced edges 	<ul style="list-style-type: none"> 1 pint bottle 12 bottles/carton 100 lineal feet per pint @ 1/8" diameter bead 	24 lbs/carton
Walkway Rolls	<ul style="list-style-type: none"> 125 mil extruded and embossed TPO Gray Only 	<ul style="list-style-type: none"> Herringbone traction surfacing in gray color Available in rolls Heat welds directly to membrane or installed with seam tape 	<ul style="list-style-type: none"> 30" x 50' 	118 lbs/roll

- Notes: 1. Mass and dimensions stated are nominal unless otherwise indicated.
2. Store accessory flashing materials in original carton, rolls, or sheets on pallets or shelving in a dry area.

Product	Description	Benefit/Application	Quantity/Size	Weight
TPO Cover Tape	<ul style="list-style-type: none"> • 30 mil TPO membrane laminated to white butyl tape 	<ul style="list-style-type: none"> • For use in stripping in primed galvanized edge metal • For use in 10 & 15 year guarantees only 	<ul style="list-style-type: none"> • 6" x 100' roll • 2 rolls/carton 	50 lbs/carton
Preformed Split Pipe Boots	<ul style="list-style-type: none"> • Boots are fabricated from 45 mil thick reinforced TPO membranes 	<ul style="list-style-type: none"> • Three standard sizes are split to accommodate most common pipes and conduits 	6 Boots/carton Stock Sizes 1"-2" 3"-5" 6"-8" Special order Size 9" - 11"	7.5 lbs/carton 7.5 lbs/carton 11 lbs/carton 11 lbs/carton
RTA (Roof Transition Anchor) Strip	<ul style="list-style-type: none"> • 6" x 100' 45 mil reinforced TPO membrane with pressure sensitive adhesive • White only 	<ul style="list-style-type: none"> • To be installed on horizontal surfaces Using plates and fasteners as a base attachment in fully adhered and Freedom™ systems 	6" x 100' rolls 2 rolls/carton	34 lbs/carton
Corner Curb Wraps	<ul style="list-style-type: none"> • Corners are fabricated from 45 mil thick rein- • forced TPO membrane 	<ul style="list-style-type: none"> • Four Standard sizes to flash curbs that are 24", 36", 48" and 60" in size. • Four corners are required to flash the curb. 	4 Curb Wraps/carton. Stock Sizes are: 13.5" 19.5" 25.5" 31.5" Special order sizes: 7.5" 37.5"	5.6 lbs/carton 7.4 lbs/carton 10.7 lbs/carton 12.5 lbs/carton
Preformed Expansion Joint Covers	<ul style="list-style-type: none"> • 60 mil thick reinforced TPO membrane • White only 	<ul style="list-style-type: none"> • 5 standard sizes to accommodate most applications • Two convenient styles available to accommodate both Roof-to-Roof and Roof-to-Wall applications. 	Sizes are 4", 6", 8", 10", 12" Bellows 50 foot rolls	Ranges from 50-65 lbs.
EverGuard SA TPO Standing Seam Profile	<ul style="list-style-type: none"> • 1-1/2" wide x 1-1/4" high x 10' in length profile with pressure sensitive adhesive and release liner • White, Tan, Gray, Regal Red, Regal Blue, Hartford Green 	<ul style="list-style-type: none"> • Applied over TPO roofing systems to simulate standing seam metal roof. • Factory applied adhesive and release liner for easy installation on primed surfaces. • Butt end aligned with dowels provided with the profiles 	10' lengths 30 profiles/carton with connecting dowels	47 lbs/carton
Freedom 5'-0" Dual HW (Heat Weld) Flashing	<ul style="list-style-type: none"> • 45 mil and 60 mil reinforced membranes 	<ul style="list-style-type: none"> • Eliminates wasted membrane because of the two HW edges. • 6" HW edge allows for more flexibility and easier installation 	5' x 50'	76 lbs
EverGuard TPO Fluted Corner	<ul style="list-style-type: none"> • 8" diameter nominal 50 mil non-reinforced TPO membrane 	<ul style="list-style-type: none"> • For use in flashing outside corner of base and curb flashings 	20 Corners/carton	3 lbs/carton

Product	Description	Benefit/Application	Quantity/Size	Weight
Square Tube Wraps	<ul style="list-style-type: none"> • Square tube wraps are fabricated from 45 mil thick reinforced TPO membrane 	<ul style="list-style-type: none"> • Fast efficient alternative to field fabrication • Tube wraps are split with a designed overlap so they can be wrapped around square or rectangular tubing and ensure a solid weld • Available in three standard sizes 	6 Tube Wraps per carton Three Sizes: 4" x 4" 4" x 6" 6" x 6"	6-7 lbs/carton
Inside Corners	<ul style="list-style-type: none"> • Inside Corners are formed using unreinforced membrane to a nominal 50 mil thickness 	<ul style="list-style-type: none"> • Manufactured to accommodate inside corners of base and curb flashings • Designed for ease of welding in tight areas 	20 Corners per carton 6" x 6" x 5 1/4"	3.5 lbs/carton
Pourable Sealer Pocket	<ul style="list-style-type: none"> • Pourable Sealer Pocket is molded with TPO compound to a nominal 70 mil thickness • White Only 	<ul style="list-style-type: none"> • Provides a structural foundation for application of EverGuard Pourable Sealant with primer or a non-shrinking grout • Lower cost than coated metal fabricated pockets • Ideal for waterproofing irregular shaped roof penetrations • Pocket can be split and flashed with detailing membrane for applications around continuous pipes or penetrations 	6 Pockets per carton 9" x 6" x 4" oval with 3" base flange	6.5 lbs/carton
Drain	<ul style="list-style-type: none"> • Spun Aluminum drain preflashed with 55 mil unreinforced TPO membrane • White Only 	<ul style="list-style-type: none"> • For use in waterproofing low slope roof drains • Fast efficient alternative to field fabrication 	3 Drains per carton 10 sizes available: 1 1/2" to 6" in half inch increments	3.25 – 3.70 lbs/carton
Scupper	<ul style="list-style-type: none"> • Manufactured out of TPO Coated Metal and 55 mil unreinforced membrane • White Only 	<ul style="list-style-type: none"> • For use in waterproofing wall scuppers • Eliminates unnecessary flashing to waterproof the wall opening 	2 Scuppers per carton 4" x 6" x 12" 8" x 10" x 12"	5-9 lbs/carton
Vent	<ul style="list-style-type: none"> • Manufactured out of reinforced 45 mil TPO membrane and galvanized steel • White only 	<ul style="list-style-type: none"> • For use in venting low slope mechanically attached roofs • Limited to one-way flow to avoid moisture buildup within the roofing structure and material 	2 Vents per carton	12 lbs/carton