



- 24 GAUGE CONTINUOUS HOOK STRIP SECURED WITH DRILL-TEC™ FASTENERS @ 12" O.C.
- EVERGUARD® COATED METAL GRAVEL STOP WITH HEMMED EDGE
- GALVANIZED ANGULAR RING SHANK NAIL @ 4" O.C. STAGGERED OR DRILL-TEC™ SCREWS 12" O.C.
- HEAT WELDED LAP
- WOOD NAILER, 5/4" X 4" MIN. SECURED TO DECK
- EVERGUARD® 8" WIDE MEMBRANE FLASHING STRIP
- HEAT WELDED LAP
- EVERGUARD® FREEDOM MEMBRANE

- ENERGYGUARD™ ROOF INSULATION
- ROOF DECK/SUBSTRATE

**NOTE:**

1. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES (REFER TO DETAIL FD 115).



**GRAVEL STOP COATED METAL ROOF EDGE**

ROOF EDGE SERIES

HEATWELD ONLY

DRAWING #  
**202**

SCALE  
N.T.S.

SYSTEM  
**FD**

ISSUE/ REVISION DATE  
**3-1-10**