

Timberline® Prestique® High Definition® 40,
Timberline® Prestique® High Definition® 30,
Timberline® Prestique® High Definition®
Lifetime, Timberline® Natural Shadow™,
Timberline® ArmorShield™ II, Timberline®
Prestique® Cool Colors, Timberline® Cool
Series

Materials Data Safety Sheet #2093
Updated 11/16/09



Your Best and Safest Choice™ ...
Quality You Can Trust Since 1886!



SECTION 1: PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: Timberline® Prestique® High Definition® 40, Timberline® Prestique® High Definition® 30, Timberline® Prestique® High Definition® Lifetime, Timberline® Natural Shadow™, Timberline® ArmorShield™ II, Timberline® Prestique® Cool Colors, Timberline® Cool Series

TRADE NAME: N/A

CHEMICAL NAME / SYNONYM: N/A

CHEMICAL FAMILY: Asphalt / Fiberglass Shingles

MANUFACTURER: GAF Materials Corporation

ADDRESS: 1361 Alps Road, Wayne, NJ 07470

24-HOUR EMERGENCY PHONE (CHEMTREC): 800 – 424 – 9300

INFORMATION ONLY: 800 – 766 – 3411

PREPARED BY: Corporate EHS

APPROVED BY: Corporate EHS

NFPA Hazard Rating

HMIS Hazard Rating

Health	1
Flammable	1
Reactive	0
Special Hazards	-

1
1
0
-

Health	1
Flammable	1
Reactive	0
Personal Protection	A

1
1
0
A

OSHA HAZARDOUS: Yes

No

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

CHEMICAL NAME	CAS #	%	OSHA	ACGIH	OTHER
Granules	-	20 – 45	NE	NE	NE

OCCUPATIONAL EXPOSURE LIMITS

CHEMICAL NAME	CAS #	%	OSHA	ACGIH	OTHER
Limestone	1317-65-3	25 – 45	5 mg/m ³ – resp. 15 mg/m ³ – total	3 mg/m ³ – resp. 10 mg/m ³ – total	REL: 5 mg/m ³ – resp. 10 mg/m ³ – total
Asphalt	8052-42-4	10 – 30	NE	0.5 mg/m ³ (inhalable fraction, as benzene-soluble aerosol)	5 mg/m ³ – Ceiling (15 min. fumes)
Crystalline Silica	14808-60-7	0 – 10	10 mg/m ³ / (% SiO ₂ + 2) – resp.	0.025 mg/m ³	REL: 0.05 mg/m ³ – resp.
Fiberglass Mat	65997-17-3	1 – 3	1 f/cc – resp.	1 f/cc – resp.	REL: 5 mg/m ³ – total fibers

NE = Not Established

As defined in the OSHA Hazard Communication Standard, 29 CFR 1910.1200, the products above are considered articles and do not require an MSDS. However, GAF would like to disclose as much health and safety information as possible to ensure that this product is handled properly. All components listed for this product are bound within the shingle. When handled as intended and under normal conditions, none of the ingredients should be released and should not pose a significant health risk.

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE OF EXPOSURE: Occasional nuisance dust, Inhalation

SIGNS & SYMPTOMS OF EXPOSURE

Eyes: May cause irritation to the eyes.

Skin: May cause irritation to the skin.

Ingestion: This product is not intended to be ingested. If ingested, it may cause temporary irritation to the gastrointestinal (digestive) tract.

Inhalation: May cause irritation to the respiratory tract.

ACUTE HEALTH HAZARDS: None known.

CHRONIC HEALTH HAZARDS: None known.

CARCINOGENICITY: Direct implantation of glass fibers into the lung tissue of laboratory animals has produced lung fibrosis and lung cancer. Human epidemiological studies of inhalation exposure have yielded negative results. NTP Listed; Carcinogen IARC Class 3. Note:

Fiberglass is completely encapsulated in the product. If handled under normal conditions, fiberglass should not be released.

The International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) have determined that there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite. In addition, IARC has determined that there is sufficient evidence for the carcinogenicity of quartz and cristobalite in experimental animals. Among individuals with silicosis, lung cancer occurs more frequently in those who smoke.

The International Agency for Research on Cancer (IARC) has determined that there is limited or inadequate evidence in humans for the carcinogenicity of exposure to asphalt. Classified as a Group 2B (Possibly Carcinogenic to Humans).

SECTION 4: FIRST AID MEASURES

FIRST AID PROCEDURES

EYES: Hold eyelids open and wash with gentle stream of water for at least 15 minutes preferably at eyewash fountain.

SKIN: Wash affected area thoroughly with soap and water.

INHALATION: Remove to fresh uncontaminated air.

INGESTION: Not expected to be ingested.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: No information available

SECTION 5: FIRE FIGHTING PROCEDURES

SUITABLE EXTINGUISHING MEDIA: Water spray, Alcohol foam, Carbon Dioxide, or Dry chemical.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide and carbon monoxide.

RECOMMENDED FIRE FIGHTING PROCEDURES: NIOSH-approved self contained breathing apparatus is recommended for smoke protection, but not required.

UNUSUAL FIRE & EXPLOSION HAZARDS: N/A

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Pick up or sweep up large pieces. Avoid creating dusts during clean up.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: No specific handling or storage requirements.

OTHER PRECAUTIONS: None

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS / VENTILATION: N/A

RESPIRATORY PROTECTION: N/A

EYE PROTECTION: Safety glasses with side shields

SKIN PROTECTION: Cotton or leather gloves are recommended when handling

OTHER PROTECTIVE EQUIPMENT: None

WORK HYGIENIC PRACTICES: Wash exposed skin prior to eating, drinking or smoking and at the end of each shift.

EXPOSURE GUIDELINES: N/A

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR:	Granule coated shingle; no appreciable odor.		
FLASH POINT:	> 550 °F	LOWER EXPLOSIVE LIMIT:	No data
METHOD USED:	No data	UPPER EXPLOSIVE LIMIT:	No data
EVAPORATION RATE:	No data	BOILING POINT:	No data
pH (undiluted product):	No data	MELTING POINT:	No data
SOLUBILITY IN WATER:	No data	SPECIFIC GRAVITY:	No data
VAPOR DENSITY:	No data	PERCENT VOLATILE:	No data
VAPOR PRESSURE:	No data	MOLECULAR WEIGHT:	No data

U.S. DOT TRANSPORTATION

PROPER SHIPPING NAME: This product is not classified as a hazardous material for transport.

HAZARD CLASS: N/A

ID NUMBER: N/A

PACKING GROUP: N/A

LABEL STATEMENT: N/A

OTHER: N/A

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA: This product and its components are listed on the TSCA 8(b) inventory.

CERCLA: None

SARA

311 / 312 HAZARD CATEGORIES: None

313 REPORTABLE INGREDIENTS: Asphalt 8052-42-4

CALIFORNIA PROPOSITION 65: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.
Cancer: Asphalt.

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

Chemical Name	CAS #	CA	MA	MN	NJ	PA	RI
Limestone	1317-65-3	No	Yes	Yes	No	Yes	Yes
Asphalt	8052-42-4	Yes	Yes	Yes	Yes	Yes	Yes
Crystalline Silica	14808-60-7	Yes	Yes	Yes	Yes	Yes	Yes
Fiberglass Mat	65997-17-3	Yes	No	Yes	Yes	No	Yes

SECTION 16: OTHER INFORMATION

ADDITIONAL COMMENTS:	None.
DATE OF PREVIOUS MSDS:	October 2008
CHANGES SINCE PREVIOUS MSDS:	Added Timberline® Cool Series to prodct name section (November 2009); Added Timberline® ArmorShield™ II to the product name section (October 2008)

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.