

FOR JOBS UP TO 50 SQUARES ONLY

EVERGUARD® DOUBLE-SIDED TAPE EXTEND BEYOND CORNER 1" (25 mm)
 EVERGUARD® TPO UNIVERSAL CORNER

REINFORCED EVERGUARD® MEMBRANE
 PRIME FIELD MEMBRANE WITH EVERGUARD® TPO LOW VOC PRIMER. SHOULD EXTEND 1" OUT PAST STRIP-IN TAPE.

LINE UNDERSIDE OF EVERGUARD® UNIVERSAL CORNER WITH EVERGUARD® DOUBLE-SIDED TAPE

PRIME EVERGUARD® TPO UNIVERSAL CORNER WITH EVERGUARD® TPO LOW VOC PRIMER.

NOTE: PRIME ENTIRE CORNER PRIOR TO STRIPPING IN WITH EVERGUARD® STRIP-IN TAPE (NOT SHOWN)

COVER EVERGUARD® UNIVERSAL CORNER WITH EVERGUARD® STRIP-IN TAPE. PRIME AREA UNDERNEATH STRIP-IN TAPE PRIOR TO INSTALLING.

NOTE:

1. APPLY FLEXSEAL™ CAULK GRADE SEALANT TO ALL EVERGUARD® STRIP-IN TAPE EDGES AND ALL CUT REINFORCED TPO EDGE.
2. MEMBRANE MUST BE PRIMED AND DRY PRIOR TO APPLYING EVERGUARD® DOUBLE SIDED TAPE.



DRAWING #
739

OUTSIDE CORNER REINFORCEMENT - UNIVERSAL CORNER DETAIL

THIS DETAIL APPLIES TO:
Taped Seam Systems

www.gaf.com
 1 Campus Drive,
 Parsippany, NJ 07054

SCALE
 N.T.S.

REVISION DATE
 5-1-15