






FORTIFIED Roof™ Estimating Legend with Xactimate line items*

		GAF Product(s)†	Xactimate Line Item	CAT	SEL
1. NAIL IT DOWN	BETTER ATTACHMENT				
	<ul style="list-style-type: none"> - Use 8D ring-shank nails to fasten decking to framing - Nail with tighter spacing than typical code requires 	N/A	Re-nailing of roof sheathing - complete re-nail	RFG	RENAIL+
2. TAPE IT UP	SEALED ROOF DECK Choose one option:				
	Option 1: Tape seams + synthetic deck protection	GAF Roof Deck Seam Tape	Water barrier joint taping - Mod. bitumen - 4" seam tape	RFG	WBT
		Deck-Armor™ TigerPaw™ FeltBuster®	Roofing felt - synthetic underlayment	RFG	FELTSU
	Option 2: Two layers deck protection	Deck-Armor™ TigerPaw™ FeltBuster®	Roofing felt - synthetic und. - double coverage/low slope	RFG	FELLSU
		StormGuard®	Ice & water barrier - High temp	RFG	IWSHT
	Option 3: Self-adhered membrane on full deck.	WeatherWatch®	Ice & water barrier	RFG	IWS
3. LOCK IT IN	STRONGER EDGES				
	<ul style="list-style-type: none"> - Minimum 26 gauge for steel drip edge - Install drip edge over deck protection, with tighter nail spacing - Use either a fully adhered starter strip or set starter in 8"- wide flashing cement 	N/A	Drip Edge	RFG	DRIP
			and/or for eaves: Drip edge/gutter apron	RFG	DRIP>
	Option 1: Fully adhered starter	QuickStart®	Asphalt starter - peel and stick	RFG	ASTR
	Option 2: Flashing cement + Starter Strip shingle (choose one)	LIBERTY™ Flashing Cement	Apply roofing sealant/ cement - per LF	RFG	SEAL
		WeatherBlocker™ Pro-Start®	Asphalt starter - universal starter course	RFG	ASTR-
		StarterMatch® Note: Installed in conjunction with WeatherBlocker™	Asphalt starter - laminated double layer starter	RFG	ASTR+

* Please note that pricing information for GAF products provided by Xactimate or Cotality™ software may not reflect actual prices.

† This information is provided for informational purposes only and is subject to change. It is your responsibility to independently verify the information before relying on it. GAF will not be held liable for any errors or omissions contained herein. Eligibility requirements, terms and restrictions apply to the FORTIFIED program. See current FORTIFIED home standard and technical resources at fortifiedspecs.org. U.S. only. For information about the GAF and IBHS alliance and GAF products that can be used to comply with certain FORTIFIED requirements visit gaf.com/fortified. Even if GAF products meet certain FORTIFIED requirements or are used in a FORTIFIED designated roof, GAF products are covered by GAF's limited warranties, which provide your sole and exclusive remedy for any covered issues arising out of or related to qualifying GAF products. See gaf.com/warranties for details.

For more training and estimating resources,
visit gaf.com/StormTraining

We protect what matters most™





FORTIFIED Roof™ Estimating Legend with Xactimate line items*

Shingle Requirements†		GAF Product(s)†	Xactimate Line Item	CAT	SEL
HIGH WIND/HURRICANE STANDARD	Class F (ASTM D3161) or Class H (ASTM D7158) rated asphalt shingles	GAF offers a wide array of shingles that comply with the FORTIFIED™ requirements. See the full list of shingles and Xactimate codes at gaf.com/XactimateRoof		RFG	Varies by product
		Seal-A-Ridge®	Hip / Ridge cap - Standard profile - composition shingle	RFG	RIDGCS
		Z®Ridge TimberTex®	Hip / Ridge cap - High profile - composition shingles	RFG	RIDGC+
OPTIONAL HAIL SUPPLEMENT	If seeking the optional hail supplement under the FORTIFIED™ Home High Wind or Hurricane designations, asphalt shingles must be rated Good or Excellent in the IBHS Hail Impact Standard Ratings	Timberline® AS II Shingles	Laminated - High grd - impact resist shingle	RFG	400IS
		Seal-A-Ridge® AS SBS-Modified IR Ridge Cap Shingles OR TimberCrest® Premium SBS-Modified Ridge Cap Shingles	Hip / Ridge cap - impact resistant composition shingles	RFG	RIDGCI
VENTILATION	All ridge and off-ridge roof vents must be tested in accordance with TAS 100 (A)	See qualifying GAF ventilation products that meet the criteria of the FORTIFIED™ Program at gaf.com/FORTIFIED and associated Xactimate line items at gaf.com/XactimateRoof			

* Please note that pricing information for GAF products provided by Xactimate or Cotality™ software may not reflect actual prices.

† This information is provided for informational purposes only and is subject to change. It is your responsibility to independently verify the information before relying on it. GAF will not be held liable for any errors or omissions contained herein. Eligibility requirements, terms and restrictions apply to the FORTIFIED program. See current FORTIFIED home standard and technical resources at fortifiedspecs.org. U.S. only. For information about the GAF and IBHS alliance and GAF products that can be used to comply with certain FORTIFIED requirements visit gaf.com/fortified. Even if GAF products meet certain FORTIFIED requirements or are used in a FORTIFIED designated roof, GAF products are covered by GAF's limited warranties, which provide your sole and exclusive remedy for any covered issues arising out of or related to qualifying GAF products. See gaf.com/warranties for details.




For more training and estimating resources,
visit gaf.com/StormTraining

We protect what matters most™





FORTIFIED Roof™ Estimating Legend with Cotality Estimate™ (Symbility) line items

		GAF Product(s) [†]	Cotality™ Line Item
1. NAIL IT DOWN	BETTER ATTACHMENT		
	<ul style="list-style-type: none">- Use 8D ring-shank nails to fasten decking to framing- Nail with tighter spacing than typical code requires	N/A	Add-on, Roof Sheathing, Re-nail, FORTIFIED
2. TAPE IT UP	SEALED ROOF DECK Choose one option:		
	Option 1: Tape seams + synthetic deck protection	Deck-Armor™ TigerPaw™ FeltBuster®	Felt, Single Layer, #30, FORTIFIED* *seam tape is included
	Option 2: Two layers deck protection	Deck-Armor™ TigerPaw™ FeltBuster®	Felt, Double Coverage, #30, FORTIFIED
	Option 3: Self-adhered membrane on full deck	StormGuard® WeatherWatch®	Ice/Water Shield, SF, FORTIFIED
3. LOCK IT IN	STRONGER EDGES		
	<ul style="list-style-type: none">- Minimum 26 gauge for steel drip edge- Install drip edge over deck protection, with tighter nail spacing- Use either a fully adhered starter strip or set starter in 8" wide flashing cement	N/A	<ul style="list-style-type: none">- Drip Edge, Eave/Rake, FORTIFIED, High Wind Zone- Drip Edge, Eave/Rake, FORTIFIED, Hurricane Zone
	Option 1: Fully adhered starter	QuickStart®	Shingles, Starter Row, Continuous, FORTIFIED
	Option 2: Flashing cement + Starter Strip shingle (choose one)	LIBERTY™ Flashing Cement	Roof Cement, 8" Wide
		WeatherBlocker™ Pro-Start®	Shingles, Starter Row, Continuous
	StarterMatch® Note: Installed in conjunction with WeatherBlocker™	Shingles, Starter Row, High Performance, Designer	

* Please note that pricing information for GAF products provided by Xactimate or Cotality™ software may not reflect actual prices.

[†] This information is provided for informational purposes only and is subject to change. It is your responsibility to independently verify the information before relying on it. GAF will not be held liable for any errors or omissions contained herein. Eligibility requirements, terms and restrictions apply to the FORTIFIED program. See current FORTIFIED home standard and technical resources at fortifiedspecs.org. U.S. only. For information about the GAF and IBHS alliance and GAF products that can be used to comply with certain FORTIFIED requirements visit gaf.com/fortified. Even if GAF products meet certain FORTIFIED requirements or are used in a FORTIFIED designated roof, GAF products are covered by GAF's limited warranties, which provide your sole and exclusive remedy for any covered issues arising out of or related to qualifying GAF products. See gaf.com/warranties for details.

For more training and estimating resources, visit gaf.com/StormTraining

We protect what matters most™





FORTIFIED Roof™ Estimating Legend with Cotality Estimate™ (Symbility) line items

Shingle Requirements†		GAF Product(s)†	Cotality™ Line Item
Class F (ASTM D3161) or Class H (ASTM D7158) rated asphalt shingles	Non-coastal high wind / hurricane option	GAF offers a wide array of shingles that comply with the FORTIFIED™ requirements. See the full list of shingles and line items at gaf.com/CotalityRoof	Selected shingle line item + Add-on, FORTIFIED™ Roof Nailing Pattern, Galvanized Nails, Fiberglass/Asphalt Shingles
	Coastal High wind / hurricane option		Selected shingle line item + Add-on, FORTIFIED™ Roof Nailing Pattern, Hot-Dipped Galvanized Nails, Fiberglass/Asphalt Shingles
	Coastal High wind / hurricane option (Salt water exposure areas)		Selected shingle line item + Add-on, FORTIFIED™ Roof Nailing Pattern, Stainless Steel Nails, Fiberglass/Asphalt Shingles
		Seal-A-Ridge®	Ridge Cap Shingles, Laminated/Architectural
		Z®Ridge TimberTex®	Ridge Cap Shingles, Composition, High Profile
OPTIONAL HAIL SUPPLEMENT	If seeking the optional hail supplement under the FORTIFIED™ Home High Wind or Hurricane designations, asphalt shingles must be rated Good or Excellent in the IBHS Hail Impact Standard Ratings	Timberline® AS II Shingles	Shingles, Laminated/Architectural Very Good + Add-on, Impact-Resistant, Fiberglass/Asphalt Shingles
		Seal-A-Ridge® AS SBS Modified IR Ridge Cap Shingles OR TimberCrest® Premium SBS-Modified Ridge Cap Shingles	Ridge Cap Shingles, Laminated/Architectural + Add-on, Impact-Resistant, Fiberglass/Asphalt Ridge Cap Shingles OR Ridge Cap Shingles, Composition, High Profile + Add-on, Impact-Resistant, Fiberglass/Asphalt Ridge Cap Shingles
VENTILATION	All ridge and off-ridge roof vents must be tested in accordance with TAS 100 (A)	See the many GAF ventilation products that meet the criteria of the FORTIFIED™ Program at gaf.com/FORTIFIED and associated Cotality line items at gaf.com/CotalityRoof	

* Please note that pricing information for GAF products provided by Xactimate or Cotality™ software may not reflect actual prices.

† This information is provided for informational purposes only and is subject to change. It is your responsibility to independently verify the information before relying on it. GAF will not be held liable for any errors or omissions contained herein. Eligibility requirements, terms and restrictions apply to the FORTIFIED program. See current FORTIFIED home standard and technical resources at fortifiedspecs.org. U.S. only. For information about the GAF and IBHS alliance and GAF products that can be used to comply with certain FORTIFIED requirements visit gaf.com/fortified. Even if GAF products meet certain FORTIFIED requirements or are used in a FORTIFIED designated roof, GAF products are covered by GAF's limited warranties, which provide your sole and exclusive remedy for any covered issues arising out of or related to qualifying GAF products. See gaf.com/warranties for details.

For more training and estimating resources, visit gaf.com/StormTraining

We protect what matters most™

