

LEXUCO® Metal Edge Flashing

Updated: 8/16



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*



LEXSUCO[®] METAL EDGE FLASHING

Description

Lexsuco[®] Metal Edge Flashing consists of the Lexsuco[®] Reinforced Flashings (RF) with a 1 1/2" (38 mm) strip of galvanized metal laminated to one (1) edge or two (2) edges. The Metal Edge Flashing is available in 12" (305 mm), 18" (457 mm), and 24" (610 mm) widths. Technical and sales information can be obtained through GAF Technical Services at (800) 766-3411.

Uses

Deck: Lexsuco[®] Metal Edge Flashing is installed using plastic cement or steep asphalt for adhesion.

Parapet Walls: Lexsuco[®] Metal Edge Flashing is installed using plastic cement or steep asphalt for adhesion in addition to mechanical fasteners and CA-103 adhesive for extensions exceeding 12" (305 mm) above roof deck. Mechanical fasteners are placed through the metal, which acts as a termination bar.

Applicable Standards

GAF products are listed or approved by the following agencies or code bodies:

Underwriters Laboratories (UL),
and ULC (Canada)

Factory Mutual (FM)

Int'l Council Bldg. Officials (ICBO)

Southern Bldg. Code Congress Int'l (SBCCI)

Miami-Dade County Product Control Approved

Product Specifications (nominal)

Data Is Per:	50' Roll (12" width)
Membrane Length	50 ft (15.24 m)
Membrane Width	12 in (305 mm)
Membrane Weight*	18 lb (8.16 kg)
Membrane Thickness	40 mils
Coverage Per Roll	50 lineal feet (15.24 lm)

*Does not include weight of metal edging.

Data reported based on available independent and in-house resources. GAF reserves the right to change or modify, at its discretion, and without prior notice, any of the information, requirements, specifications or policies contained in this document.

Property (ASTM D5147)	Test Method	Test Results
Tensile Strength, psi	ASTM D412	1750 psi
Water Absorption	ASTM D570	<0.4% by weight
Low Temperature Flex	ASTM D2136	Passed -20° F (-28.9 °C)
Adhesive Strength 12 in. (305 mm)/min.	ASTM D903	10 lb./in. peel
Breaking Strength	ASTM D751-68	>130 lb./in.
Tear strength	ASTM D751-68	>40 lbs. (18.1 kg)
Fire Resistance	ASTM D1692-68	Self-extinguishing
Asphalt compatibility	160°F (71.1 °C) for one month	Excellent