

LEXUCO® Black/White Flexible Vinyl Flashing

Updated: 8/16



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*



LEXSUCO® BLACK/WHITE FLEXIBLE VINYL FLASHING

Description

Lexsuco® Black/White Flexible Vinyl Flashing is a two-ply, 60-mil non-reinforced polymer flashing. The Lexsuco® Black/White Flashings are available in 12' (3.7 m), 18' (5.5 m), 24' (7.31 m), and 36' (11 m) widths.

Application

Decks: Lexsuco® Black/White Flexible Vinyl Flashing is installed using plastic cement or steep asphalt for adhesion.

Parapet Walls: Lexsuco® Black/White Flexible Vinyl Flashing is installed using plastic cement or steep asphalt for adhesion, in addition to termination bar and CA-103 adhesive for extensions exceeding 12' (3.7 m) above roof deck. Refer to the complete application instructions for Lexsuco® Black/White Flexible Vinyl Flashing on gaf.com.

Advantages

- High tensile strength and a high degree of dimensional stability, resulting in a roof system with greater resistance to splitting and cracking
- Optimum porosity of the felt provides ready escape of air while allowing proper asphalt penetration at the time of mopping
- Asphalt coating provides high degree of moisture resistance

For Application Questions

Contact GAF Technical Services at 1-800-766-3411 or visit gaf.com.



Property	Test Method	Test Results
Tensile Strength	ASTM D412	1350
Elongation	ASTM D412	2%
Tension Set, 50% Extension	ASTM D412	5%
Low Temperature	ASTM D1790	No crack % -10°F (-23.3 °C)