


PLATE WELDED DETAIL

TPO= YELLOW PLATE
PVC= BLACK PLATE



RHINOBOND® 3" (76 mm) PLATE

REINFORCED EVERGUARD®
MEMBRANE (SMOOTH ONLY)

DRILL-TEC™ RHINOBOND®
FASTENER AND PLATE

GAF APPROVED COVERBOARD OR
SECOND LAYER OF INSULATION IF
REQUIRED. SEE NOTE 2

ENERGYGUARD™
ROOF INSULATION

METAL DECK

APPROVED FLUTE FILLER
IF REQUIRED

AIR/VAPOR RETARDED
-AS REQUIRED

NOTE:

1. REFER TO THE DRILL-TEC™ RHINOBOND® ATTACHMENT TABLES FOR DETAILED INSTALLATION REQUIREMENTS REGARDING DECK TYPE, PLATE & FASTENER TYPE, AND MIN. EMBEDMENT.
2. TOP LAYER OF INSULATION DOES NOT HAVE TO BE STAGGERED IF BASE LAYER IS STAGGERED.



EverGuard
SINGLE-PLY ROOFING SYSTEMS
ROOF PENETRATION
SERIES

DRAWING #
100E

**DRILL-TEC™ RHINOBOND® ASSEMBLY
DETAIL**

THIS DETAIL APPLIES TO:
**RHINOBOND®
ATTACHMENT
SYSTEMS**

www.gaf.com
1 Campus Drive,
Parsippany, NJ 07054

SCALE
N.T.S.

REVISION DATE
11-15-16