



24-GAUGE CONTINUOUS HOOK STRIP SECURED WITH DRILL-TEC™ FASTENERS @ 12" (305 mm) O.C.

EVERGUARD® COATED METAL EDGE

RING SHANK GALVANIZED NAIL @ 4" (102 mm) O.C. STAGGERED OR DRILL-TEC™ SCREWS 12" (305 mm) O.C. 2" (52 mm) MINIMUM FROM OUTSIDE EDGE OF METAL.

HEAT-WELDED LAP

WOOD NAILER, 5/4" (31.8 mm) x 4" (102 mm) MIN. SECURED TO DECK

8" (203 mm) WIDE EVERGUARD® FLASHING STRIP HEAT-WELDED

HEAT-WELDED LAP

REINFORCED EVERGUARD® MEMBRANE (PERIMETER SHEET IF REQUIRED)

FOR ALTERNATE TAPERED ROOF EDGE, USE ENERGYGUARD™ TAPERED INSULATION

ENERGYGUARD™ ROOF INSULATION

ROOF DECK/SUBSTRATE

**NOTE:**

1. FOR INSULATION THICKNESS GREATER THAN 8" (203 mm), A HARD BOARD IS REQUIRED ON MECHANICALLY FASTENED SYSTEMS ONLY.
2. 25-YEAR GUARANTEES AND ABOVE MUST USE EXTREME ACCESSORIES.
3. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES (REFER TO EVERGUARD® DETAIL 115).



DRAWING #  
**202A**  
SCALE  
N.T.S.

**COATED METAL ROOF EDGE DETAIL**

**THIS DETAIL APPLIES TO:**  
Adhered Systems  
Self-Adhered Systems  
TriPosite Systems  
Mechanically Attached Systems

REVISION DATE  
**6-20-16**