

FRONT SIDE OF PARAPET WALL

FASTEN SCUPPER MEMBRANE ON FRONT SIDE OF PARAPET WALL WITH EVERGUARD® TERMINATION BAR (OPTIONAL)

REFER TO PARAPET AND WALL DETAIL FOR TERMINATION

EVERGUARD® COATED METAL WITH HEMMED EDGE

DRILL-TEC™ FASTENERS 12" (305 mm) O.C. (AT LEAST 1 ON EVERY PLANE)

REINFORCED EVERGUARD® MEMBRANE OR EVERGUARD® DETAIL MEMBRANE

PREMANUFACTURED OUTSIDE CORNERS - HEAT WELDED OR UNREINFORCED FIELD FABRICATED CORNERS HEAT WELDED

DRILL-TEC™ PLATES & SCREWS 12" (305 mm) O.C. (6" [152 mm] O.C. FOR BALLASTED SYSTEMS)

REINFORCED EVERGUARD® MEMBRANE (PERIMETER SHEET IF REQUIRED)

ENERGYGUARD™ ROOF INSULATION

ROOF DECK/SUBSTRATE

HEAT-WELDED LAP

WOOD NAILER 5/4" (38.1 mm) x 4" (102 mm) MIN. SECURED TO DECK (OPTIONAL)

**NOTE:**

1. DETAIL TO BE USED IN CONJUNCTION WITH STANDARD GUIDE SPECIFICATION CONTAINING REQUIREMENTS FOR NAILERS, INSULATION ETC.
2. FOR INSULATION THICKNESS GREATER THAN 8" (203 mm), A HARD BOARD IS REQUIRED ON MECHANICAL SYSTEMS ONLY.
3. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES (REFER TO EVERGUARD® DETAIL 115).



**EverGuard**  
SINGLE-PLY ROOFING SYSTEMS  
PARAPET WALL &  
CURB SERIES

DRAWING #

**322**

SCALE  
N.T.S.

**SCUPPER - FIELD FABRICATED  
OPEN TOP DETAIL**

**THIS DETAIL APPLIES TO:**  
Adhered Systems  
Ballasted Systems  
Mechanically Attached Systems  
Self-Adhered Systems  
(Heat-Weld Only)  
TriPosite Systems

REVISION DATE  
**5-24-16**

www.gaf.com  
1 Campus Drive,  
Parsippany, NJ 07054