

# **EverGuard® PVC 60 mil Fleece-Back Membrane Data Sheet**

Updated: 8/17



*Quality You Can Trust...From  
North America's Largest Roofing Manufacturer!™*

# EverGuard® PVC 60 mil Fleece-Back Membrane

## Applicable Standards ASTM D4434 Type IV, UL Listed, FM Approved

Physical Properties	Test Method	ASTM Minimum	EverGuard® PVC 60 mil Fleece-back Membrane Typical Test Data
1. Certain data is provided in MD (machine direction) x CMD (cross machine direction) format. 2. Data is based upon typical product performance, and is subject to normal manufacturing tolerance and variance.			
Nominal Thickness	ASTM D751	.045" (1.14 mm)	0.06" (1.52 mm)
Thickness over Scrim	ASTM D7635	0.016" (0.40 mm)	0.025" (0.64 mm)
Breaking Strength	ASTM D751	200 lbf (298 kg/m) (MD & CMD)	>370 lbf (550 kg/m)
Elongation at Break	ASTM D751	15% (MD & CMD)	25%
Seam Strength	ASTM D751	75% (Percentage of tensile or breaking strength)	Pass
Tear Strength	ASTM D751	45 lbf (MD & CMD) (67 kg/m)	Pass
Low Temperature Bend	ASTM D2136	-40°C	Pass
Accelerated Weathering	ASTM G154 <sup>†</sup>	Pass	>38,360 kJ/m <sup>2</sup>
Dimensional Stability	ASTM D1204	≤0.50%	0.30%
Change in Weight after Water Immersion	ASTM D570	+/-3%	Pass
Static Puncture Resistance	ASTM D5602	Pass	Pass
Dynamic Puncture Resistance	ASTM D5635	Pass	Pass
Breaking Strength after Heat Aging	ASTM D3045	90%	Pass
Elongation at Break after Heat Aging	ASTM D3045	90%	Pass
Solar Reflective Index (SRI)	ASTM E903	N/A	110
Solar Reflectivity (White) Initial/Aged*	ASTM C1549	N/A	0.87/0.806
Emissivity (White) Initial/Aged*	ASTM E903	N/A	0.88/0.89

<sup>†</sup>At an irradiance level of 1.55 W/(m<sup>2</sup>.nm) at 340 nm  
\*Using CRRC Rapid Ratings

## Product Data

<b>Roll Size</b>	Note: Product sizes, dimensions, and widths are nominal values and are subject to normal manufacturing/packaging tolerance and variation.				
	<b>Colors</b>	<b>Full Sheet</b>	<b>Full-Roll Weight</b>	<b>Half Sheet</b>	<b>Half-Roll Weight</b>
	White	120" x 100' (3.05 m x 30.5 m)	392.5 lb. (178.0 kg)	60" x 100' (1.52 m x 30.5 m)	196.25 lb. (89.0 kg)
<b>Storage</b>	Note: Membrane rolls shipped horizontally on pallets, stacked in a pyramid.				
<b>Safety Warning</b>	Membrane rolls are heavy. Position and install by at least two people.				

Contact your local representative for details

RhinoBond® is a registered trademark of OMG.