

GAF EverGuard® TPO Coated SpeedTite™ Drain Sell Sheet

Updated: 4/16



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*

gaf.com

Description

EverGuard[®] TPO single-ply roofing system preflashed accessories provide roofing contractors an easy-to-install factory-built detail. EverGuard[®] preflashed accessories are constructed using GAF's proven, durable EverGuard[®]TPO single-ply detailing membrane.

- Cost Effective... Reduces installed costs by up to 25% compared to field-fabricated accessories
- Improved Reliability... Factory-built accessories reduce risk of leaks and callbacks
- Improved Aesthetics... Uniform look

Application

EverGuard[®] TPO preflashed accessories are designed for use with GAF EverGuard[®] TPO single-ply membranes and EverGuard[®] Freedom[™] TPO self-adhering membranes. The preflashed accessories may be installed on mechanically attached, fully adhered, or self-adhered EverGuard[®] TPO roofing systems. Preflashed accessories are installed using conventional techniques. See published application and specifications manual for detailed instructions.

Product Information

With the GAF SpeedTite[™] Mechanical Seal and "drop-in-ready" packaging, the GAF SpeedTite[™] Roof Drain is the fastest installed drain on the market. The SpeedTite[™] Roof Drain has been designed with a maximum inside diameter drain stem designed for improved flow performance.



Coated SpeedTite[™] Drain

- The GAF SpeedTite[™] Mechanical Seal (patent pending) can be made watertight in seconds without using any tools
- Installs in half the time of other insert drains, enhancing productivity
- The hand-tightened seal activator creates a symmetrical watertight connection
- One-piece seamless body provides strength and durability
- Extra-large flange allows positive attachment of roof flashing membrane
- Heavy-duty cast aluminum strainer dome and clamping ring
- Exceeds ANSI/SPRI RD1 for back flow prevention for improved flow performance
- Also available with a TPO- or PVC-coated flange for hot-air weld flashing

SPECIFICATIONS		
Drain Body	11-gauge 0.125" (3.18 mm) spun aluminum	
Flange	17½" (445 mm) diameter with sump area	
Stem	10" (254 mm) length	
SHIPPING SPECIFICATIONS		
	3" (76 mm)	4" (102 mm)
Drains per carton:	1	1
Weight per carton:	8.5 lb. (3.86 kg)	8.9 lb. (4.04 kg)
Cartons per pallet:	20	20
PRODUCT SKUS		
3" (76 mm)	8523R	
4" (102 mm)	8523S	

Quality You Can Trust... From North America's Largest Roofing Manufacturer![™]

gaf.com

Visit gaf.com to see our full line of prefabricated accessories!