

GAFGLAS® Ply 4 Ply Sheet

Updated: 8/16



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*



GAFGLAS[®]

PLY 4 PLY SHEET

Description

GAFGLAS[®] Ply 4 Ply Sheet roofing felt is constructed with a strong glass fiber mat that is coated with the finest quality asphalt, and is designed with optimum porosity to ensure a sound, watertight membrane.

Uses

GAFGLAS[®] Ply 4 Ply Sheet is used as a ply felt in the construction of built-up roofs. It is designed for use in all climate zones and is appropriate for use as a base sheet, as a ply felt, and in the construction of flashing membranes.

Advantages

- High tensile strength and a high degree of dimensional stability, resulting in a roof system with greater resistance to splitting and cracking.
- Optimum porosity of the felt provides ready escape of air while allowing proper asphalt penetration at the time of mopping.
- Asphalt coating provides high degree of moisture resistance.
- Fire resistant—for use in UL Class A rated assemblies.
- Wind uplift resistance—selected roofing assemblies with GAFGLAS[®] Ply 4 felts meet FM Class 1-180 when installed over concrete decks.

Advantages (Continued)

- Meets ASTM D2178, Type IV specifications.
- Meets requirements for application in all climate zones.
- Rolls out flat for easy installation.
- System guarantees available for up to 15 years; select system constructions available with up to 20-year guarantee coverage.*

Applicable Standards

Meets ASTM D2178, Type IV
FM Approved
ICC ESR-1274
Miami-Dade County Product Control Approved
UL/ULC Listed

Product Specifications (nominal)

Roll Size	5 squares (531 gross sq. ft.) (49.3 m ²)
Roll Length	161.8' (49.3 m)
Roll Width	39.375" (1.0 m)
Approx. Roll Weight	34.9 lb (20.0 kg)



* See applicable guarantee for complete coverage and restrictions.