

GAFGLAS® Stratavent Perforated Venting Base Sheet

Updated: 8/16



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*



GAFGLAS®

STRATAVENT® PERFORATED VENTING BASE SHEET

Formerly GAFGLAS® Stratavent® Eliminator™
Perforated Venting Base Sheet

Description

GAFGLAS® Stratavent® Perforated Venting Base Sheet is a premium-grade roofing felt constructed around a strong glass fiber mat and high-quality asphalt. The bottom of the sheet is granule-surfaced to provide positive venting of any trapped gases under the roof membrane.

- GAFGLAS® Stratavent® Perforated Venting Base Sheet is available for nailable and non-nailable substrates.
- GAFGLAS® Stratavent® Perforated Venting Base Sheet is unique in the industry: its patent-pending perforated design allows mopping asphalt to flow through to the substrate as the next ply of the roof system is installed. The flow-through asphalt uniformly bonds the GAFGLAS® Stratavent® Perforated Venting Base Sheet and the subsequent roof system to the substrate.

Uses

GAFGLAS® Stratavent® Perforated Venting Base Sheet is a venting base sheet designed to be used in various GAFGLAS® built-up and RUBEROID® modified bitumen roofing systems. It can be used over both nailable and non-nailable substrates, including certain existing old roof surfaces and isocyanurate foams.



Advantages

- Provides for venting of pressurized gases beneath the roofing membrane.
- Fire resistant—for use in UL, ULC Class A rated assemblies.
- In re-cover applications, provides an effective means for separating the new roofing membrane from the existing roof system.
- GAFGLAS® Stratavent® Perforated Venting Base Sheet provides consistent, uniform spot-attachment of the roofing membrane.
- Wind uplift-resistant; FM Approved up to Class 1-345 (see FM Approval Guide for details).
- Meets requirements for application in all climate zones.
- System guarantees are available for up to 20 years.*

Applicable Standards

Meets ASTM D4897, Type II
FM Approved
ICC ESR-1274
Miami-Dade County Product Control Approved
State of Florida Approved
Texas Department of Insurance
UL/ULC Listed

Product Specifications (nominal)

Roll Size	1.26 squares (133.4 gross sq. ft.) (12.4 m ²)
Roll Length	40.6' (12.4 m)
Roll Width	39.375" (1.0 m)
Approx. Roll Weight	76 lb (34.5 kg)

* See applicable guarantee for complete coverage and restrictions.