



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786) 315-2590 F (786) 315-2599

[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

## NOTICE OF ACCEPTANCE (NOA)

**GAF**

**1 Campus Dr.  
Parsippany, NJ 07054**

### SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

**DESCRIPTION: HydroStop® PremiumCoat® Roof Maintenance Coating Systems.**

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state, model/ series and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA No.15-0812.01 and consists of pages 1 through 12.  
The submitted documentation was reviewed by Gaspar J Rodriguez.



NOA No.: 16-0309.01  
Expiration Date: 06/21/21  
Approval Date: 10/27/16  
Page 1 of 12

## ROOFING COMPONENT APPROVAL

Category: Roofing  
Sub-Category: Cement-Adhesive-Coatings  
Material: Elastomeric

### SCOPE:

This approves “**HydroStop® PremiumCoat® Roof Maintenance Coating Systems**” as a maintenance roof coating system, as manufactured by GAF, as described in this Notice of Acceptance, designed to comply with the Florida Building Code and the High Velocity Hurricanes Zone of the Florida Building Code.

### TRADE NAMES OF PRODUCTS MANUFACTURED OR LABELED BY APPLICANT:

**TABLE 1**

<u>Product</u>	<u>Container Sizes</u>	<u>Test Specification</u>	<u>Product Description</u>
<b>United Cleaning Concentrate</b> <i>Manufacturing Location #4</i>	2 & 5 Gallon	Proprietary	Biodegradable cleaning agent with specific functional ingredients for degreasing and removing soils and biological residues for proper cleaning of roof surfaces.
<b>CleanAct Rinsable Primer</b> <i>Manufacturing Location #7</i>	2 & 5 Gallon	Proprietary	Water based, rinseable primer used directly on rubber roof (EPDM) applications.
<b>Adhere-It® II Primer</b> <i>Manufacturing Location #7</i>	2 & 5 Gallon	Proprietary	Water based, rinseable primer used directly on rubber roof (EPDM) applications.
<b>HydroStop® BarrierGuard® Waterproofing</b> <i>Manufacturing Location #1</i>	2 & 5 Gallon	Proprietary	Priming and waterproofing compound for masonry surfaces.
<b>SureBond Primer</b> <i>Manufacturing Locations #1 &amp; #2</i>	2 & 5 Gallon	Proprietary	Acrylic primer for masonry and chalky surfaces.
<b>Unibase Primer</b> <i>Manufacturing Location #2</i>	5 Gallon	Proprietary	Low viscosity, highly penetrating, acrylic primer for modified bitumen, BUR and previously coated surfaces that also acts as an excellent asphalt bleed blocker.
<b>TPO Red Primer</b> <i>Manufacturing Location #3</i>	5 Gallon	Proprietary	Solvent-based primer for TPO membranes.
<b>XR-2000 Primer</b> <i>Manufacturing Location #3</i>	5 Gallon	Proprietary	Water-based Acrylic primer for Kynar coated metal.
<b>Lock-Down Primer</b> <i>Manufacturing Location #5</i>	1 & 5 Gallon	Proprietary	Moisture-cure urethane primer for corrosion protection on metal surfaces.
<b>Acrylex 400 Primer</b> <i>Manufacturing Location #2</i>	1 & 5 Gallon	Proprietary	Acrylic latex primer for use over metal, masonry and wood surfaces.



**TRADE NAMES OF PRODUCTS MANUFACTURED OR LABELED BY APPLICANT:**

**TABLE 1**

<u>Product</u>	<u>Container Sizes</u>	<u>Test Specification</u>	<u>Product Description</u>
<b>Epoxy Primer</b> Manufacturing Location #2	1 & 5 Gallon	Proprietary	Single component epoxy primer/sealer designed to penetrate and seal porous surfaces.
<b>FlexSeal™ Sealant</b> Manufacturing Location #3	1 & 5 Gallon or 1 qt. Tube	TAS 139	Solvent-based, elastomeric sealant.
<b>HydroStop® PremiumCoat® Foundation Coat</b> Manufacturing Locations #1& #2	2 & 5 Gallon	Proprietary	Acrylic elastomeric waterproofing compound used as a base layer in the HydroStop® PremiumCoat® System.
<b>HydroStop® PremiumCoat® Fabric</b> Manufacturing Location #6	Rolls	Proprietary	Reinforcing fabric for the HydroStop® PremiumCoat® System.
<b>HydroStop® HydroCap Fastener Fabric</b> Manufacturing Location #6	Box	Proprietary	4 in. diameter, non-woven, stitch bonded polyester fabric disc with center cut hole for flashing exposed fasteners in the HydroStop® PremiumCoat® System.
<b>HydroStop® PremiumCoat® Butter Grade Flashing</b> Manufacturing Location #2	2 & 5 Gallon	Proprietary	Acrylic elastomeric sealant for bridging gaps, filling voids and low lying roof areas.
<b>United Coatings™ Roof Mate TCM Flashing</b> Manufacturing Location #3	2 & 5 Gallon	TAS 139	Water based, high solids, elastomeric sealant.
<b>United Coatings™ Roof Mate Liquid Fabric</b> Manufacturing Location #3	5 & 55 Gallon	TAS 139	Water based, sprayable highly elastic flashing compound.
<b>HydroStop® PremiumCoat® FinishCoat</b> Manufacturing Locations #1& #2	2 & 5 Gallon	ASTM D6083	Acrylic elastomeric waterproofing compound used as a top layer in the HydroStop® PremiumCoat® System.
<b>HydroStop® TrafficCoat Deck Coating</b> Manufacturing Locations #1& #2	2 & 5 Gallon	Proprietary	Acrylic elastomeric waterproofing compound used as non-skid surfacing layer over the HydroStop® PremiumCoat® System.



**MANUFACTURING LOCATIONS:**

1. Charleston, SC
2. Phoenix, AZ
3. Walpole, MA
4. Olympia, WA
5. Richmond, MO
6. Spartanburg, SC
7. Fountain Inn, SC

**EVIDENCE SUBMITTED:**

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
FM Approvals	3000150	FM 4470	09/22/99
	3023606	FM 4470	10/18/06
	3046086	FM 4470	01/18/13
	FM RR204674	FM 4470	03/23/16
Trinity ERD	SC10845.04.16	TAS 114	04/26/16
PRI Construction Materials Technologies, LLC	GAF-508-02-01	Proprietary	03/12/14
	GAF-658-02-01	Proprietary	06/07/17
	GAF-659-02-01	Proprietary	06/03/16
	GAF-660-02-01	Proprietary	06/03/16
	GAF-661-02-01	Proprietary	06/03/16
	GAF-662-02-01	Proprietary	06/07/16
	GAF-663-02-01	Proprietary	06/03/16
	GAF-664-02-01	Proprietary	06/03/16
	GAF-665-02-01	Proprietary	06/03/16
	GAF-667-02-01	TAS 139	07/01/16
	GAF-668-02-01	TAS 139	07/01/16
	GAF-671-02-01	TAS 139	07/01/16
	GAF-674-02-01	Proprietary	06/01/16
	GAF-675-02-01	Proprietary	06/01/16
	GAF-676-02-01	Proprietary	06/01/16
	GAF-677-02-01	Proprietary	06/01/16
	GAF-678-02-01	Proprietary	07/14/16
	GAF-679-02-01	Proprietary	06/01/16
	GAF-680-02-01	Proprietary	06/01/16
	GAF-687-02-01	ASTM C 794	06/06/16
	GAF-688-02-01	ASTM C 794	06/06/16
	GAF-712-02-01	Proprietary	07/21/16
	GAF-693-02-01	ASTM D 1876	06/22/16
	GAF-693-02-02	ASTM D 1876	06/22/16
HSI-007-02-01	ASTM D 6083	05/20/16	
HSI-009-02-01	ASTM D 6083	05/20/16	
Underwriters Laboratories	TGFU.R26758	UL790	02/09/16



## PHYSICAL PROPERTIES OF COMPONENTS:

**Trade name:** HydroStop® BarrierGuard® Waterproofing

**Specification:** Proprietary

**Description:** Mixed with water and Portland cement (as per GAF's published installation instructions), HydroStop® BarrierGuard® Waterproofing forms a hard-wearing, flexible compound, and fully reinforced with HydroStop® PremiumCoat® Fabric, it produces an excellent heavy traffic system for decks.

**Container Size:** 2 and 5 gallons. Note all cautions on container label.

**Trade name:** HydroStop® PremiumCoat® Foundation Coat

**Specification:** Proprietary

**Description:** An acrylic, elastomeric waterproofing compound used as a base coat in the HydroStop™ PremiumCoat® System, applied with or without HydroStop® PremiumCoat® Fabric per GAF's published installation instructions.

**Container Size:** 2 and 5 gallons. Note all cautions on container label.

**Trade name:** HydroStop® PremiumCoat® FinishCoat

**Specification:** ASTM D6083

**Description:** Acrylic elastomeric waterproofing compound applied as a finish coat in the HydroStop® PremiumCoat® System per GAF's published installation instructions.

**Container Size:** 2 and 5 gallons. Note all cautions on container label.



## APPROVED SUBSTRATES:

**Substrate:** Existing Galvanized Metal Roof Panel System

**All Limitations apply.**

HydroStop® products shall be installed in accordance with the manufacturer's specifications. The following are minimum installation guidelines. Consult the manufacturer's specifications or Technical Representative for specific/complete installation instructions.

**Preparation:** The surface shall be clean, sound and dry prior to application of the coating. All surface preparation shall be in compliance with the coating manufacturer's published application instructions and current Miami-Dade County Product Control Notice of Acceptance.

**Base Coat:** HydroStop® PremiumCoat® Foundation Coat shall be applied to the entire substrate at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Fabric & Coat:  
(Optional)** Embed HydroStop® PremiumCoat® Fabric into the wet HydroStop® PremiumCoat® Foundation Coat base coat within minimum 4" wide seams and then saturate the HydroStop® PremiumCoat® Fabric with HydroStop® PremiumCoat® Foundation Coat applied at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Flashing:** At all seams, joints or laps embed a single layer of HydroStop™ PremiumCoat® Fabric in the wet HydroStop® PremiumCoat® Foundation Coat base coat, overlapping fabric seams a minimum of 4".

On all exposed fasteners, embed a 6 x 6 in. piece of HydroStop® PremiumCoat® Fabric or a HydroStop® HydroCap Fastener Cap into the wet HydroStop® PremiumCoat® Foundation Coat base coat.

Fully saturate all HydroStop® PremiumCoat® Fabric and HydroStop® HydroCap Fastener Caps with additional HydroStop® PremiumCoat® Foundation Coat applied at a minimum rate of 1.25gal/sq.

Flashing details for all penetrations, seams, laps, exposed fasteners and transitions shall be in accordance with GAF's published installation instructions.

**Finish Coats:** HydroStop® PremiumCoat® FinishCoat shall be applied in two or more coats. Each coat shall be applied at a minimum rate of 0.75 gal/sq. Each coat shall be allowed to dry prior to application of subsequent coats.



**Substrate:** Existing Built-Up Roof (BUR) or Modified Bitumen Roof

**All Limitations apply.**

HydroStop® products shall be installed in accordance with the manufacturer's specifications. The following are minimum installation guidelines. Consult the manufacturer's specifications or Technical Representative for specific/complete installation instructions.

**Preparation:** The surface shall be clean, sound and dry prior to application of the coating. All surface preparation shall be in compliance with the coating manufacturer's published application instructions and current Miami-Dade County Product Control Notice of Acceptance.

**Base Coat:** HydroStop® PremiumCoat® Foundation Coat shall be applied to the entire substrate at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Fabric & Coat:** Embed HydroStop® PremiumCoat® Fabric into the wet HydroStop™ PremiumCoat® Foundation Coat base coat within minimum 4" wide seams and then saturate the HydroStop™ PremiumCoat® Fabric with HydroStop® PremiumCoat® Foundation Coat applied at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Flashing:** Flashing details for all penetrations, seams, laps and transitions shall be in accordance with GAF's published installation instructions.

**Finish Coats:** HydroStop® PremiumCoat® FinishCoat shall be applied in two or more coats. Each coat shall be applied at a minimum rate of 0.75 gal/sq. Each coat shall be allowed to dry prior to application of subsequent coats.

**Substrate:** New or Existing Smooth SBS Modified Bitumen Roof

**All Limitations apply.**

HydroStop® products shall be installed in accordance with the manufacturer's specifications. The following are minimum installation guidelines. Consult the manufacturer's specifications or Technical Representative for specific/complete installation instructions.

**Preparation:** The surface shall be clean, sound and dry prior to application of the coating. All surface preparation shall be in compliance with the coating manufacturer's published application instructions and current Miami-Dade County Product Control Notice of Acceptance.

**Base Coat:** HydroStop® PremiumCoat® Foundation Coat shall be applied to the entire substrate at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Fabric & Coat:** Embed HydroStop® PremiumCoat® Fabric into the wet HydroStop™ PremiumCoat® Foundation Coat base coat within minimum 4" wide seams and then saturate the HydroStop™ PremiumCoat® Fabric with HydroStop® PremiumCoat® Foundation Coat applied at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Flashing:** Flashing details for all penetrations, seams, laps and transitions shall be in accordance with GAF's published installation instructions.

**Finish Coats:** HydroStop® PremiumCoat® FinishCoat shall be applied in two or more coats. Each coat shall be applied at a minimum rate of 0.75 gal/sq. Each coat shall be allowed to dry prior to application of subsequent coats.





**Substrate: New or Existing Spray Applied Polyurethane Foam (SPUF)**

**All Limitations apply.**

HydroStop® products shall be installed in accordance with the manufacturer's specifications. The following are minimum installation guidelines. Consult the manufacturer's specifications or Technical Representative for specific/complete installation instructions.

**Preparation:** The surface shall be clean, sound and dry prior to application of the coating. All surface preparation shall be in compliance with the coating manufacturer's published application instructions and current Miami-Dade County Product Control Notice of Acceptance.

**Base Coat:** HydroStop® PremiumCoat® Foundation Coat shall be applied to the entire substrate at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Fabric & Coat:** Embed HydroStop® PremiumCoat® Fabric into the wet HydroStop® PremiumCoat® Foundation Coat base coat within minimum 4" wide seams and then saturate the HydroStop® PremiumCoat® Fabric with HydroStop® PremiumCoat® Foundation Coat applied at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Flashing:** Flashing details for all penetrations, seams, laps and transitions shall be in accordance with GAF's published installation instructions.

**Finish Coat:** HydroStop® PremiumCoat® FinishCoat shall be applied in two or more coats. Each coat shall be applied at a minimum rate of 0.75 gal/sq. Each coat shall be allowed to dry prior to application of subsequent coats.

**Substrate: New or Existing Single-Ply Membrane: PVC**

**All Limitations apply.**

HydroStop® products shall be installed in accordance with the manufacturer's specifications. The following are minimum installation guidelines. Consult the manufacturer's specifications or Technical Representative for specific/complete installation instructions.

**Preparation:** The surface shall be clean, sound and dry prior to application of the coating. All surface preparation shall be in compliance with the coating manufacturer's published application instructions and current Miami-Dade County Product Control Notice of Acceptance.

**Base Coat:** HydroStop® PremiumCoat® Foundation Coat shall be applied to the entire substrate at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Fabric & Coat:** Embed HydroStop® PremiumCoat® Fabric into the wet HydroStop® PremiumCoat® Foundation Coat base coat within minimum 4" wide seams and then saturate the HydroStop® PremiumCoat® Fabric with HydroStop® PremiumCoat® Foundation Coat applied at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Flashing:** Flashing details for all penetrations, seams, laps and transitions shall be in accordance with GAF's published installation instructions.

**Finish Coat:** HydroStop® PremiumCoat® FinishCoat shall be applied in two or more coats. Each coat shall be applied at a minimum rate of 0.75 gal/sq. Each coat shall be allowed to dry prior to application of subsequent coats.





**Substrate:** New or Existing Single-Ply Membrane: TPO

**All Limitations apply.**

HydroStop® products shall be installed in accordance with the manufacturer's specifications. The following are minimum installation guidelines. Consult the manufacturer's specifications or Technical Representative for specific/complete installation instructions.

**Preparation:** The surface shall be clean, sound and dry prior to application of the coating. All surface preparation shall be in compliance with the coating manufacturer's published application instructions and current Miami-Dade County Product Control Notice of Acceptance.

**Primer:** Membrane shall be primed with TPO Red Primer applied at 0.5 gal/sq.

**Base Coat:** HydroStop® PremiumCoat® Foundation Coat shall be applied to the entire substrate at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Fabric & Coat:** Embed HydroStop® PremiumCoat® Fabric into the wet HydroStop® PremiumCoat® Foundation Coat base coat within minimum 4" wide seams and then saturate the HydroStop® PremiumCoat® Fabric with HydroStop® PremiumCoat® Foundation Coat applied at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Flashing:** Flashing details for all penetrations, seams, laps and transitions shall be in accordance with GAF's published installation instructions.

**Finish Coat:** HydroStop® PremiumCoat® FinishCoat shall be applied in two or more coats. Each coat shall be applied at a minimum rate of 0.75 gal/sq. Each coat shall be allowed to dry prior to application of subsequent coats.

**Substrate:** New or Existing Single-Ply Membrane: EPDM

**All Limitations apply.**

HydroStop® products shall be installed in accordance with the manufacturer's specifications. The following are minimum installation guidelines. Consult the manufacturer's specifications or Technical Representative for specific/complete installation instructions.

**Preparation:** The surface shall be clean, sound and dry prior to application of the coating. All surface preparation shall be in compliance with the coating manufacturer's published application instructions and current Miami-Dade County Product Control Notice of Acceptance.

**Base Coat:** HydroStop® PremiumCoat® Foundation Coat shall be applied to the entire substrate at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Fabric & Coat:** Embed HydroStop® PremiumCoat® Fabric into the wet HydroStop® PremiumCoat® Foundation Coat base coat within minimum 4" wide seams and then saturate the HydroStop® PremiumCoat® Fabric with HydroStop® PremiumCoat® Foundation Coat applied at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Flashing:** Flashing details for all penetrations, seams, laps and transitions shall be in accordance with GAF's published installation instructions.

**Finish Coat:** HydroStop® PremiumCoat® FinishCoat shall be applied in two or more coats. Each coat shall be applied at a minimum rate of 0.75 gal/sq. Each coat shall be allowed to dry prior to application of subsequent coats.



**Substrate:**           **Structural Concrete with Optional Primer**

**All Limitations apply.**

HydroStop® products shall be installed in accordance with the manufacturer's specifications. The following are minimum installation guidelines. Consult the manufacturer's specifications or Technical Representative for specific/complete installation instructions.

**Preparation:**       The surface shall be clean, sound and dry prior to application of the coating. All surface preparation shall be in compliance with the coating manufacturer's published application instructions and current Miami-Dade County Product Control Notice of Acceptance.

**Primer:**               Epoxy Primer applied at 0.4 gal/sq or SureBond Primer applied at 0.4 gal/sq  
**(Optional)**

**Base Coat:**         HydroStop® PremiumCoat® Foundation Coat shall be applied to the entire substrate at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Fabric & Coat:**    Embed HydroStop® PremiumCoat® Fabric into the wet HydroStop® PremiumCoat® Foundation Coat base coat within minimum 4" wide seams and then saturate the HydroStop® PremiumCoat® Fabric with HydroStop® PremiumCoat® Foundation Coat applied at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Flashing:**         Flashing details for all penetrations, seams, laps and transitions shall be in accordance with GAF's published installation instructions.

**Finish Coat:**      HydroStop® PremiumCoat® FinishCoat shall be applied in two or more coats. Each coat shall be applied at a minimum rate of 0.75 gal/sq. Each coat shall be allowed to dry prior to application of subsequent coats.



**Substrate:**                    **Structural Concrete with Surface Treatment and Optional Primer**

**All Limitations apply.**

HydroStop® products shall be installed in accordance with the manufacturer's specifications. The following are minimum installation guidelines. Consult the manufacturer's specifications or Technical Representative for specific/complete installation instructions.

**Preparation:**                The surface shall be clean, sound and dry prior to application of the coating. All surface preparation shall be in compliance with the coating manufacturer's published application instructions and current Miami-Dade County Product Control Notice of Acceptance.

**Surface Treatment:**      HydroStop® BarrierGuard® Waterproofing applied in two (2) coats at a rate of 0.67 gal./sq. per coat.

**Primer:  
(Optional)**                    SureBond Primer applied at 0.4 gal/sq

**Base Coat:**                    HydroStop® PremiumCoat® Foundation Coat shall be applied to the entire substrate at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Fabric & Coat:**              Embed HydroStop® PremiumCoat® Fabric into the wet HydroStop® PremiumCoat® Foundation Coat base coat within minimum 4" wide seams and then saturate the HydroStop® PremiumCoat® Fabric with HydroStop® PremiumCoat® Foundation Coat applied at a minimum rate of 1.25 gal/sq with approved roof brushes.

**Flashing:**                    Flashing details for all penetrations, seams, laps and transitions shall be in accordance with GAF's published installation instructions.

**Finish Coat:**                HydroStop® PremiumCoat® FinishCoat shall be applied in two or more coats. Each coat shall be applied at a minimum rate of 0.75 gal/sq. Each coat shall be allowed to dry prior to application of subsequent coats.



## **BUILDING PERMIT REQUIREMENTS:**

1. This Notice of Acceptance.
2. Any other documents required by the Building Official or applicable Building Code in order to properly evaluate the installation of this system.
3. Approved Applicator Certificate (designated by GAF) listing the contractor & approved applicator's name.

## **LIMITATIONS:**

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. Contractor must be a GAF HydroStop® "Approved Applicator", trained and familiar with the details and specifications published by the manufacturer. The proper application and installation of all HydroStop™ products shall be the sole responsibility of the contractor.
3. Refer to GAF's published installation instructions for detailed installation requirements and recommendations.
4. HydroStop™ products shall not be applied in inclement weather conditions.
5. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to Miami-Dade Product Control upon request. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.
6. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
7. The HydroStop® PremiumCoat® System shall be used as a roof maintenance coating system in accordance with applicable Building Code.
8. The HydroStop® PremiumCoat® System shall not be covered with stone chips, screeds, tiles or soil.
9. Approved primer is required on all unprotected iron and steel and previously painted surfaces.
10. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance.
11. The HydroStop® PremiumCoat® System shall not be applied over gravel surfaces.
12. HydroStop® TrafficCoat Deck Coating is required for all traffic bearing surfaces: All pedestrian traffic areas shall be covered with HydroStop® TrafficCoat Deck Coating as skid resistant surfacing.
13. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



**END OF THIS ACCEPTANCE**

