

SAFETY DATA SHEET



1. Identification

Product identifier UNITILE LV SEALER PART A

Other means of identification
Product Code

Recommended use Epoxy polyamide penetrating primer/sealer.

Manufacturer/Importer/Supplier/Distributor information Manufacturer

Company name GAF
1 Campus Drive
Parsippany, NJ 07054 USA

Telephone 1-800-766-3411

Emergency phone number CHEMTREC [DAY OR NIGHT] 1-800-424-9300
Within USA and CANADA 1-800-424-9300

Outside USA and Canada: 1 703-741-5970

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Carcinogenicity	Category 2
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word

Danger

Hazard statement

Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. Suspected of causing cancer. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

Storage

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
4,4'-Isopropylidenediphenol-Epichlorohydrin Copolymer		25068-38-6	60 to <70
Xylene		1330-20-7	10 to <20
ETHYLBENZENE		100-41-4	5 to <10
Methyl isobutyl ketone		108-10-1	1 to <5
TOLUENE		108-88-3	0.1 to <1
Other components below reportable levels			10 to <20

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO ₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe the mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
ETHYLBENZENE (CAS 100-41-4)	PEL	435 mg/m3
		100 ppm
Methyl isobutyl ketone, MIBK (CAS 108-10-1)	PEL	410 mg/m3
		100 ppm
Xylene (CAS 1330-20-7)	PEL	435 mg/m3
		100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm
Methyl isobutyl ketone, MIBK (CAS 108-10-1)	STEL	75 ppm
	TWA	20 ppm
TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
ETHYLBENZENE (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
Methyl isobutyl ketone, MIBK (CAS 108-10-1)	TWA	435 mg/m3
		100 ppm
	STEL	300 mg/m3
TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)		75 ppm
	TWA	205 mg/m3
		50 ppm
	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Methyl isobutyl ketone, MIBK (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*
TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
Xylene (CAS 1330-20-7)	0.02 mg/l	Toluene	Blood	*
	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3) Skin designation applies.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties**Appearance**

Physical state Liquid.

Form Liquid.

Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -138.82 °F (-94.9 °C) estimated

Initial boiling point and boiling range 276.98 °F (136.1 °C) estimated

Flash point 73.0 °F (22.8 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 1.2 % estimated

Flammability limit - upper (%) 6.8 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 11.19 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 810 °F (432.22 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 8.70 lbs/gal

Flammability class Flammable IB estimated

Percent volatile (by wt) 28.8 %

Specific gravity 1.04

VOC 288 g/L

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong acids. Strong oxidizing agents. Halogens.

Hazardous decomposition products

No hazardous decomposition products are known.

10. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful if inhaled. May cause an allergic skin reaction.

Components	Species	Test Results
ETHYLBENZENE (CAS 100-41-4)		
Acute		
Dermal		
LD50	Rabbit	17800 mg/kg
Oral		
LD50	Rat	3500 mg/kg
Methyl isobutyl ketone, MIBK (CAS 108-10-1)		
Acute		
Dermal		
LD50	Rabbit	> 16000 mg/kg
Inhalation		
LC50	Rat	8.2 mg/l, 4 Hours
Oral		
LD50	Rat	2080 mg/kg
TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	12124 mg/kg 14.1 ml/kg
Inhalation		
LC50	Mouse	5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours
Oral		
LD50	Rat	2.6 g/kg
Xylene (CAS 1330-20-7)		
Acute		
Dermal		
LD50	Rabbit	> 43 g/kg
Inhalation		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours

Components	Species	Test Results
Oral		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Methyl isobutyl ketone, MIBK (CAS 108-10-1)	2B Possibly carcinogenic to humans.
TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

11. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
ETHYLBENZENE (CAS 100-41-4)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 7.5 - 11 mg/l, 96 hours
Methyl isobutyl ketone, MIBK (CAS 108-10-1)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 492 - 593 mg/l, 96 hours
TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch) 8.11 mg/l, 96 hours
Xylene (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

ETHYLBENZENE	3.15
Methyl isobutyl ketone, MIBK	1.31
TOLUENE (METHYLBENZENE, TOLUOL)	2.73
Xylene	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

12. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

13. Transport information

DOT

UN number	UN1993
UN proper shipping name	Flammable liquids, n.o.s. (ETHYLBENZENE RQ = 16026 LBS, Methyl isobutyl ketone, MIBK RQ = 154799 LBS)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, T7, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242

IATA

UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (ETHYLBENZENE, Methyl isobutyl ketone, MIBK)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	Yes
ERG Code	3H
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (ETHYLBENZENE, Methyl isobutyl ketone, MIBK)
Transport hazard class(es)	
Class	3

Subsidiary risk -
Packing group II
Environmental hazards
Marine pollutant Yes
EmS F-E, S-E
Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.
Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

DOT



IATA; IMDG



Marine pollutant



General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

14. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ETHYLBENZENE (CAS 100-41-4)	Listed.
Methyl isobutyl ketone, MIBK (CAS 108-10-1)	Listed.
TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Xylene	1330-20-7	10 to <20
ETHYLBENZENE	100-41-4	5 to <10
Methyl isobutyl ketone, MIBK	108-10-1	1 to <5
TOLUENE (METHYLBENZENE, TOLUOL)	108-88-3	0.1 to <1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

ETHYLBENZENE (CAS 100-41-4)
 Methyl isobutyl ketone, MIBK (CAS 108-10-1)
 TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Methyl isobutyl ketone, MIBK (CAS 108-10-1) 6715
 TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Methyl isobutyl ketone, MIBK (CAS 108-10-1) 35 %WV
 TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Methyl isobutyl ketone, MIBK (CAS 108-10-1) 6715
 TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3) 594

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ETHYLBENZENE (CAS 100-41-4)
 Methyl isobutyl ketone, MIBK (CAS 108-10-1)
 TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

ETHYLBENZENE (CAS 100-41-4)
 Methyl isobutyl ketone, MIBK (CAS 108-10-1)
 TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

ETHYLBENZENE (CAS 100-41-4)
 Methyl isobutyl ketone, MIBK (CAS 108-10-1)
 TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

ETHYLBENZENE (CAS 100-41-4)

Methyl isobutyl ketone, MIBK (CAS 108-10-1)
TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. Rhode Island RTK

ETHYLBENZENE (CAS 100-41-4)
Methyl isobutyl ketone, MIBK (CAS 108-10-1)
TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ETHYLBENZENE (CAS 100-41-4) Listed: June 11, 2004
Methyl isobutyl ketone, MIBK (CAS 108-10-1) Listed: November 4, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methyl isobutyl ketone, MIBK (CAS 108-10-1) Listed: March 28, 2014
TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

TOLUENE (METHYLBENZENE, TOLUOL) (CAS 108-88-3) Listed: August 7, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

15. Other information, including date of preparation or last revision

Issue date	05-12-2015
Revision date	11-30-2015
Version #	02
HMIS® ratings	Health: 2* Flammability: 3 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 3 Instability: 0
Disclaimer	This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a

recommendation for uses which infringe valid patents or as extending a license of valid patents.

Revision Information

Product and Company Identification: Converted to GAF SDS
