



SECTION 1: PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: UNITED COATINGS ROOF MATE TCM COATING

TRADE NAME: N/A

**CHEMICAL NAME /
SYNONYM:** N/A

CHEMICAL FAMILY: N/A

MANUFACTURER: GAF

ADDRESS: 1 Campus Drive, Parsippany, NJ 07054

**24-HOUR EMERGENCY
PHONE (CHEMTREC):** 800 – 424 – 9300







INFORMATION ONLY: 800 – 766 – 3411

PREPARED BY: Corporate EHS

APPROVED BY: Corporate EHS

SECTION 2: HAZARD IDENTIFICATION

NFPA and HMIS RATINGS:

| | NFPA Hazard Rating | | HMIS Hazard Rating |
|---|-----------------------|---|-----------------------|
|  | 2 |  | 2 |
|  | 0 |  | 0 |
|  | 0 |  | 0 |
| Special Hazards | - | Personal Protection | X |

GHS LABEL ELEMENTS:

GHS CLASSIFICATION: Eye Irritant - Category 2A
Skin Irritant - Category 2
Target Organ (SE) - Category 3
Target Organ (RE) - Category 2
Reproductive Toxicity - Category 1A
Carcinogen - Category 2
Acute Toxicity - Category 4
Mutagenicity - Category 1B
Hazardous to the Aquatic Environment (chronic) - Category 1
Hazardous to the Aquatic Environment (acute) – Category 1



SIGNAL WORD: Danger

HAZARD STATEMENTS: May cause damage to organs through prolonged or repeated exposure
 Causes skin irritation
 Causes serious eye irritation
 May cause respiratory irritation
 Harmful if inhaled or swallowed
 May damage fertility or the unborn child
 Suspected of causing cancer
 Very toxic to aquatic life with long lasting effects

ADDITIONAL HAZARD IDENTIFICATION INFORMATION:

PRIMARY ROUTE OF EXPOSURE: Inhalation, Skin Contact, Eye Contact

SIGNS & SYMPTOMS OF EXPOSURE

EYES: Exposure to vapors can cause conjunctivitis or irritation to the eyes.

SKIN: Slight irritation of the skin. Prolonged contact can cause reddening of the skin.

INGESTION: Not expected to be ingested.

INHALATION: Vapors or mists can cause mental sluggishness, irritation of nasal passages, throat and lungs. Can cause headaches.

ACUTE HEALTH HAZARDS: Excessive exposure can cause pulmonary edema.

CHRONIC HEALTH HAZARDS: None known

CARCINOGENICITY: IARC has determined that occupational exposure to Titanium Dioxide is possibly carcinogenic to humans (Group 2B). IARC concluded lung tumors were observed in rats following high dose exposure by inhalation and in female rats exposed by intra-tracheal instillation. Other studies have shown no tumors in rats following inhalation exposure and no tumors in mice or rats following oral exposure.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| | | | OCCUPATIONAL EXPOSURE LIMITS | | |
|---------------------|------------|-----------|---|---|---|
| CHEMICAL NAME | CAS # | % (BY WT) | OSHA | ACGIH | OTHER |
| Aluminum Trihydrate | 21645-51-2 | 30 – 40 | 5 mg/m ³ – resp. 15 mg/m ³ – total | 3 mg/m ³ – resp. 10 mg/m ³ – total | REL: 5 mg/m ³ – resp., 10 mg/m ³ – total |

| | | | | | |
|------------------------------|------------|---------|---|---|--|
| Zinc Oxide | 1314-13-2 | 2 – 10 | 5 mg/m ³ – resp. 15 mg/m ³ – total | 2 mg/m ³ – resp. 10 mg/m ³ – resp. STEL | REL: 5 mg/m ³ , 15 mg/m ³ – ceiling |
| Titanium Dioxide | 13463-67-7 | 2 – 10 | 15 mg/m ³ – total | 10 mg/m ³ – total | REL: lowest feasible concentration |
| Ethylene Glycol | 107-21-1 | 2 – 10 | NE | 100 ppm – ceiling | NE |
| Non-hazardous ingredients | - | 45 – 55 | NE | NE | NE |

NE = Not Established

SECTION 4: FIRST AID MEASURES

FIRST AID PROCEDURES

- EYES:** Flush eyes with water for 15 minutes. If irritation persists, call a physician.
- SKIN:** Wash area thoroughly with soap and water.
- INHALATION:** Remove person to an area that has fresh air. If breathing has stopped, administer artificial respiration. Contact physician immediately.
- INGESTION:** If patient is awake, induce vomiting by giving two glasses of water and pressing down at back of throat. Call physician immediately. Never give anything by mouth to an unconscious person.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: Excessive exposure can cause pulmonary edema.

SECTION 5: FIRE FIGHTING PROCEDURES

- SUITABLE EXTINGUISHING MEDIA:** Water spray, CO₂, Dry chemical or foam.
- HAZARDOUS COMBUSTION PRODUCTS:** Carbon dioxide and carbon monoxide.
- RECOMMENDED FIRE FIGHTING PROCEDURES:** Self-contained breathing apparatus recommended.
- UNUSUAL FIRE & EXPLOSION HAZARDS:** None

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Dam up area to prevent spreading. Caution – area will be slippery. Use absorbent material to dry up the compound. Provide ventilation in closed areas.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Store in a well ventilated area at 50 – 80 °F.

OTHER PRECAUTIONS: Protect from freezing.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS / VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure limits.

RESPIRATORY PROTECTION: Use NIOSH-approved respirator.

EYE PROTECTION: Safety goggles or safety glasses with side shields.

SKIN PROTECTION: Wear appropriate impermeable gloves and protective clothing as necessary to prevent skin contact.

OTHER PROTECTIVE EQUIPMENT: N/A

WORK HYGIENIC PRACTICES: Wash exposed skin prior to eating, drinking, or smoking and at the end of each shift.

EXPOSURE GUIDELINES: N/A

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|--------------------------------|---------------------------------------|-------------------------------|---------|
| APPEARANCE & ODOR: | Heavy white liquid with ammonia odor. | | |
| FLASH POINT: | > 240 °F | LOWER EXPLOSIVE LIMIT: | No data |
| METHOD USED: | TCC | UPPER EXPLOSIVE LIMIT: | No data |
| EVAPORATION RATE: | 1.0 | BOILING POINT: | 212 °F |
| pH (undiluted product): | No data | MELTING POINT: | No data |
| SOLUBILITY IN WATER: | Dilutable in water | SPECIFIC GRAVITY: | 1.48 |

SECTION 14: TRANSPORTATION INFORMATION**U.S. DOT TRANSPORTATION**

PROPER SHIPPING NAME: This product is not classified as a hazardous material for transport.

HAZARD CLASS: N/A

ID NUMBER: N/A

PACKING GROUP: N/A

LABEL STATEMENT: N/A

OTHER: N/A

SECTION 15: REGULATORY INFORMATION**U.S. FEDERAL REGULATIONS**

TSCA: This product and its components are listed on the TSCA 8(b) inventory.

CERCLA: Ethylene Glycol, 107-21-1, 5,000 lbs.

SARA

311/312 HAZARD CATEGORIES: Acute Health Hazard, Chronic Health Hazard

313 REPORTABLE INGREDIENTS: None

CALIFORNIA PROPOSITION 65: None

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

| Chemical Name | CAS # | CA | MA | MN | NJ | PA | RI |
|---------------------|------------|-----|-----|-----|-----|-----|-----|
| Aluminum Trihydrate | 21645-51-2 | No | No | No | No | No | No |
| Zinc Oxide | 1314-13-2 | Yes | No | Yes | Yes | Yes | Yes |
| Titanium Dioxide | 13463-67-7 | No | No | Yes | Yes | Yes | Yes |
| Ethylene Glycol | 107-21-1 | Yes | Yes | Yes | Yes | Yes | Yes |

SECTION 16: OTHER INFORMATION

ADDITIONAL COMMENTS: None

DATE OF PREVIOUS SDS: December 2013

CHANGES SINCE PREVIOUS SDS: Conversion to Quest SDS .

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.