



SECTION 1: PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: UNITED COATINGS SURFACE SEAL SB ROOF COATING

TRADE NAME: N/A

**CHEMICAL NAME /
SYNONYM:** N/A

CHEMICAL FAMILY: N/A

MANUFACTURER: GAF

ADDRESS: 1 Campus Drive, Parsippany, NJ 07054

**24-HOUR EMERGENCY
PHONE (CHEMTREC):** 800 – 424 – 9300

INFORMATION ONLY: 800 – 766 – 3411

PREPARED BY: Corporate EHS

APPROVED BY: Corporate EHS

SECTION 2: HAZARD IDENTIFICATION

NFPA and HMIS RATINGS:

	NFPA Hazard Rating		HMIS Hazard Rating
	3		3
	3		3
	0		0
Special Hazards	-	Personal Protection	X

GHS LABEL ELEMENTS:

GHS CLASSIFICATION: Flammable Liquid - Category 2
Eye Irritant - Category 2A
Skin Irritant - Category 2
Aspiration Toxicity - Category 1
Target Organ (SE) - Category 3
Target Organ (RE) - Category 2
Reproductive Toxicity - Category 2
Hazardous to the Aquatic Environment (chronic) - Category 2

GHS PICTOGRAMS:    

SIGNAL WORD: Danger

HAZARD STATEMENTS: Extremely flammable liquid and vapor
May cause damage to organs through prolonged or repeated exposure
May cause respiratory irritation
May cause cancer
May cause genetic defects
Causes skin irritation
Harmful if inhaled
Causes serious eye irritation
May be fatal if swallowed or enters airways
May cause drowsiness or dizziness
Suspected of damaging fertility or the unborn child
Very toxic to aquatic life with long lasting effects

ADDITIONAL HAZARD IDENTIFICATION INFORMATION:

PRIMARY ROUTE OF EXPOSURE: Eye contact, Skin contact, Skin absorption, Inhalation

SIGNS & SYMPTOMS OF EXPOSURE

EYES: This material is an eye irritant. Contact with the liquid or exposure to mist or vapor may cause stinging, redness and swelling.

SKIN: This material may cause mild skin irritation. Prolonged contact may cause redness, burning and drying or cracking of the skin. Skin absorption may produce systemic toxicity.

INGESTION: Harmful or fatal if swallowed and/or vomiting occurs. Can enter lungs and cause damage. This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

INHALATION: High concentrations of vapor or mist may cause irritation of the nose and throat and signs of nervous system depression. Can cause headaches, drowsiness, dizziness, and loss of coordination. May affect liver and kidney function. Could also cause damage to the respiratory system and have myocardial effects.

ACUTE HEALTH HAZARDS: Excessive exposure can cause pulmonary edema.

CHRONIC HEALTH HAZARDS: None known.

CARCINOGENICITY: IARC has determined that occupational exposure to Titanium Dioxide is possibly carcinogenic to humans (Group 2B). IARC concluded lung tumors were observed in rats following high dose exposure by inhalation and in female rats exposed by intra-tracheal instillation. Other studies have shown no tumors in rats following inhalation exposure and no tumors in mice or rats following oral exposure.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	% (BY WT)	OCCUPATIONAL EXPOSURE LIMITS		
			OSHA	ACGIH	OTHER
Light aromatic petroleum naphtha	64742-95-6	30 – 40	NE	NE	NE
Limestone	1317-65-3	10 – 20	5 mg/m ³ – resp. 15 mg/m ³ – total	3 mg/m ³ – resp. 10 mg/m ³ – total	REL: 5 mg/m ³ – resp. 10 mg/m ³ – total
Styrene- alphamethylstyrene resin	9011-11-4	2 – 10	NE	NE	NE
Zinc Oxide	1314-13-2	2 – 10	5 mg/m ³ – resp. 15 mg/m ³ – total	3 mg/m ³ – resp. 10 mg/m ³ – total	REL: 5 mg/m ³ – resp. 10 mg/m ³ – total
Titanium Dioxide	13463-67-7	2 – 10	5 mg/m ³ – resp. 15 mg/m ³ – total	3 mg/m ³ – resp. 10 mg/m ³ – total	REL: 5 mg/m ³ – resp. 10 mg/m ³ – total
Talc	14807-96-6	2 – 10	2 mg/m ³ – resp.	20 mppcf	REL: 2 mg/m ³ – resp.
Non-hazardous ingredients	n/a	20 – 30	NE	NE	NE

NE = Not Established**SECTION 4: FIRST AID MEASURES****FIRST AID PROCEDURES**

- EYES:** Flush eyes immediately with water for 15 minutes. Call a physician.
- SKIN:** Remove contaminated clothes. Wash exposed areas with soap and water. If redness or swelling develops, seek medical assistance.
- INHALATION:** Remove to fresh air. If breathing has stopped, give artificial respiration. Call a physician.
- INGESTION:** Do not induce vomiting. Contact physician immediately. This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

**NOTES TO PHYSICIANS OR
FIRST AID PROVIDERS:**

None.

SECTION 5: FIRE FIGHTING PROCEDURES

SUITABLE EXTINGUISHING MEDIA:	Water, fog, CO ₂ , and foam.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide and carbon monoxide.
RECOMMENDED FIRE FIGHTING PROCEDURES:	Self contained breathing apparatus recommended.
UNUSUAL FIRE & EXPLOSION HAZARDS:	Material is flammable and may be ignited by flames, sparks, heat or other sources of ignition.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES:	Dam up area to prevent spreading of material. Use absorbent material to dry up liquid. Shut off all sources of open flames, electrical sparks, or static electricity.
-------------------------------------	---

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE:	Store in a well ventilated area, 50 – 80 °F. Avoid open flames, electrical sparks or static electricity.
OTHER PRECAUTIONS:	The container is hazardous when empty. Partially full or emptied container may contain explosive vapors. Do not cut, weld, or solder on/or near the container. Do not reuse “empty” container without commercial cleaning or reconditioning.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS / VENTILATION:	Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure limits.
RESPIRATORY PROTECTION:	Use NIOSH-approved respirator.
EYE PROTECTION:	Safety goggles or safety glasses with side shields.

SKIN PROTECTION:	Wear appropriate impermeable gloves and protective clothing as necessary to prevent skin contact.
OTHER PROTECTIVE EQUIPMENT:	N/A
WORK HYGIENIC PRACTICES:	Wash exposed skin prior to eating, drinking, or smoking and at the end of each shift.
EXPOSURE GUIDELINES:	N/A

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR:	Gray liquid with a paint thinner odor (may be colored).		
FLASH POINT:	105 °F	LOWER EXPLOSIVE LIMIT:	0.5%
METHOD USED:	PMCC	UPPER EXPLOSIVE LIMIT:	6.0%
EVAPORATION RATE:	0.37	BOILING POINT:	310 – 355 °F
pH (undiluted product):	No data	MELTING POINT:	No data
SOLUBILITY IN WATER:	Insoluble	SPECIFIC GRAVITY:	1.21
VAPOR DENSITY:	4.2	PERCENT VOLATILE:	No data
VAPOR PRESSURE:	2.9	MOLECULAR WEIGHT:	No data
VOC WITH WATER (LBS/GAL):	No data	WITHOUT WATER (LBS/GAL):	No data

SECTION 10: STABILITY AND REACTIVITY

THERMAL STABILITY:	STABLE <input checked="" type="checkbox"/>	UNSTABLE <input type="checkbox"/>
CONDITIONS TO AVOID (STABILITY):	None known.	
INCOMPATIBILITY (MATERIAL TO AVOID):	Strong oxidizing agents.	
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:	Carbon dioxide or carbon monoxide.	
HAZARDOUS POLYMERIZATION:	Will not occur.	

SECTION 11: TOXICOLOGICAL INFORMATION

**TOXICOLOGICAL
INFORMATION:**

No information available.

SECTION 12: ECOLOGICAL INFORMATION**ECOLOGICAL INFORMATION:**

No information available.

SECTION 13: DISPOSAL CONSIDERATIONS**WASTE DISPOSAL METHOD:**

This product, as supplied, is regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. If discarded in its purchased form, this product is a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or residue of the product remains classified a hazardous waste as per 40 CFR 261, Subpart C. State or local regulations may also apply if they differ from the federal regulation.

RCRA HAZARD CLASS:

D001, Ignitable Hazardous Waste

SECTION 14: TRANSPORTATION INFORMATION**U.S. DOT TRANSPORTATION**

PROPER SHIPPING NAME: Coating Solution
HAZARD CLASS: 3
ID NUMBER: UN 1139
PACKING GROUP: III
LABEL STATEMENT: N/A
OTHER: N/A

SECTION 15: REGULATORY INFORMATION**U.S. FEDERAL REGULATIONS****TSCA:**

This product and its components are listed on the TSCA 8(b)

inventory.

CERCLA: None.**SARA****311/312 HAZARD CATEGORIES:** Acute Health Hazard, Chronic Health Hazard, Fire Hazard**313 REPORTABLE INGREDIENTS:** None.**CALIFORNIA PROPOSITION 65:** None.

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

Chemical Name	CAS #	CA	MA	MN	NJ	PA	RI
Light aromatic petroleum naphtha	64742-95-6	No	No	No	No	No	No
Limestone	1317-65-3	No	Yes	Yes	No	Yes	Yes
Styrene-alpha-methylstyrene resin	9011-11-4	No	No	No	No	No	No
Zinc Oxide	1314-13-2	Yes	Yes	Yes	Yes	Yes	Yes
Titanium Dioxide	13463-67-7	No	No	Yes	Yes	Yes	Yes
Talc	14807-96-6	Yes	Yes	Yes	Yes	Yes	Yes

SECTION 16: OTHER INFORMATION**ADDITIONAL COMMENTS:** None.**DATE OF PREVIOUS SDS:** October 2013**CHANGES SINCE PREVIOUS SDS:** Conversion to Quest SDS.

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.