

M-BOND™ Adhesive/Sealant

Updated: 8/16



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*



M-BOND™ ADHESIVE/SEALANT

Description

M-Bond™ Adhesive/Sealant is a moisture-curing polyether roofing sealant that bonds to asphaltic membranes, concrete, steel, aluminum, wood, glass, and PVC.

Uses

Designed for use in the M-Curb™ Pitch Pocket System to seal around penetrations; also used to adhere the M-Curb™ Pitch Pocket System to the asphaltic roof. See M-Curb™ Pitch Pocket System Installation Instructions at gaf.com for more information.

Surface Preparation

All surfaces shall be clean, sound, dry, and free of loose materials like rust, oil, wax, and grease. Wipe all new metal with rubbing alcohol before sealant application.

Packaging

10.1 fl. oz. (300 ml)

Color

Black

Shelf Life

Shelf life of M-Bond™ Adhesive/Sealant is 12 months from date of manufacture when stored at 70°F (21°C) with 50% relative humidity. High temperature and high relative humidity may significantly reduce shelf life. M-Bond™ Adhesive/Sealant will not freeze under normal conditions.

Precautions

- Do not store in elevated temperatures. Elevated temperatures will reduce shelf life.
- Store unopened containers in a cool, dry area. Protect unopened containers from water, heat, and direct sunlight.
- Use only on clean, dry surfaces that are free of all surface contaminants.
- Do not apply in temperatures below 32°F (0°C).
- Do not cut or thin M-Bond™ Adhesive/Sealant.
- Cold temperatures and low humidity will slow curing.
- Do not use on TPO or Kynar® PVDF coated materials.
- Always test substrates to confirm adhesion.

For Application Questions

Contact GAF Technical Services at 1-800-766-3411 or visit gaf.com for SDS, technical data specifications, and warranty information.

