

EverGuard® TPO 3 Square Low VOC Bonding Adhesive Sell Sheet

Updated: 12/15



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*



EverGuard[®]TPO

SINGLE-PLY ROOFING SYSTEMS

Description

- EverGuard[®] TPO 3 Square Low VOC Bonding Adhesive is a contact-type bonding adhesive specially designed for bonding TPO single-ply roofing membranes and flashings to various roofing substrates.
- EverGuard[®] TPO 3 Square Low VOC Bonding Adhesive contains less than 250 grams per liter of Volatile Organic Compounds (VOCs) and has been formulated using a blend of VOC-exempt and non-exempt solvents to be in compliance with air-quality regulations for single-ply roofing adhesives.

Features and Benefits

- Low VOC (<250 g/l)
- Easy application using roller or brush
- High initial tack

Physical Properties

Base: Synthetic polymer
Solvent: VOC-compliant blend
Flash Point: 30.2°F (-1°C)
Color: Amber
Viscosity: Nominal 2,750 cps
Coverage: 50 – 60 sq. ft./gallon (1.23 – 1.47 m²/liter)
Total Solids: 25% +/-1%
VOC: <250 grams/liter
Shelf Life: 1 year, unopened
Open Time: Up to 60 minutes
Dry Time: 15 – 25 minutes, depending on weather conditions
Application: Roller, brush, or spray
Storage: Recommended storage temperature is between 60°F – 80°F. Storage for continued periods outside this temperature range may shorten shelf life.
Installation Temperature: 40°F (4°C) and rising

Ordering Information

Packaging: 5-gallon pails (18.925-liter pails)
Weight: 38 lb. (17.24 kg.)/pail
Shipping: 45 pails/pallet
SKU Number: 49 state version (7786)



3 Square Low VOC Bonding Adhesive

Low VOC
TPO Bonding Adhesive

Quality You Can Trust...From North America's Largest Roofing Manufacturer!™