



EVERGUARD® TPO

TPO Accessories

Description

EverGuard® Base Coat is a VOC-compliant, solvent-based liquid that is applied to EverGuard® TPO membranes where adhesion of EverGuard® Liquid Flashing is desired. It is slightly tinted to discern primed areas on bright white TPO membranes.

Application

- Allows application of EverGuard® Liquid Flashing to EverGuard® TPO
- VOC compliant



EverGuard® Base Coat

EVERGUARD® BASE COAT TECHNICAL DATA	
Application Rate:	0.5 gallons/100 sq. ft. (1 – 2 L/10 m ²)
Application Method:	Roller or brush
Application Temperature (air, surface):	42°F – 120°F (5.6°C – 60°C)
Drying Time (75°F [24°C], 50% RH):	Approximately 15 minutes
Wet Mil Thickness:	Up to 5
Dry Mil Thickness:	Up to 0.5
Total Solids (by weight):	2.5% ± 0.5%
Total Solids (by volume):	1%
Specific Gravity:	1.14 g/cc
Weight Per Gallon:	9.5 ± 0.5 lb. (4.31 kg ± 0.23 kg)
Viscosity (75°F [24°C]):	100 cps
Flash Point:	5°F (-15°C)
Storage:	Store in well-ventilated area at 50°F – 80°F (10°C – 27°C)
Shelf Life:	1 year
Clean-Up:	Xylene, Toluene
VOCs:	VOC compliant up to 1 gallon
SPECIFICATIONS	
Can Size:	1 gallon (3.78 L)
Carton:	4 cans
Weight per carton:	56 lb. (25.4 kg)
SKU:	779B699WP

Quality You Can Trust...From North America's Largest Roofing Manufacturer!™