

TPO Seam Cleaner Sell Sheet

Updated: 2/17



*Quality You Can Trust...From
North America's Largest Roofing Manufacturer!™*



EVERGUARD[®] TPO Accessory

TPO Accessories

Description

Used to clean exposed or contaminated seams prior to heat welding to remove any residual soap or revitalize aged membranes.

Application

- Do not use on “bag fresh” material that has been exposed for less than 12 hours unless it has been contaminated.
- Follow the guidance below for cleaning TPO:

Light Contamination — Membrane that has been exposed overnight or up to a few days to airborne debris, foot traffic, dew, or light precipitation can usually be cleaned with a white cloth moistened with EverGuard[®] TPO Cleaner. Be sure to wait for solvent to flash off prior to welding.

Dirt-Based Contamination — Membrane that is dirt encrusted will require the use of a low-residue cleaner, such as Formula 409[®], and a mildly abrasive scrubbing pad to remove the dirt. This must be followed by cleaning with a white cloth moistened with EverGuard[®] TPO Cleaner. Be sure to wait for solvent to flash off prior to welding.



Seam Cleaner

Exposure-Based Contamination

— Membrane that is weathered or oxidized will require the use of EverGuard[®] TPO Cleaner and a mildly abrasive scrubbing pad to remove the weathered/oxidized top surface layer. This must be followed by cleaning with a white cloth moistened with EverGuard[®] TPO Cleaner. Unexposed membrane left in inventory for a year or more may need to be cleaned as instructed above. Be sure to wait for solvent to flash off prior to welding.

- VOC Content of 861 grams/liter.

SPECIFICATIONS	
Can size:	1 gallon
Cans per carton:	4
Weight per case:	33 lb. (14.96 kg)
Cases per pallet:	48
Product SKU	7793

Quality You Can Trust... From North America's Largest Roofing Manufacturer!™