

# TOPCOAT® Liquid-Applied Roofing Systems

## Precote

(TOPGN160)

Updated: 7/14



*Quality You Can Trust...From  
North America's Largest Roofing Manufacturer!™*

# PRECOTE

## Description

TOPCOAT<sup>®</sup> Precote is a clear, solvent-based thermoplastic liquid to be applied as the primer/sealer coat on any areas of corrugated asbestos (Transite) panels.\* Precote is extremely flexible and durable. Like all solvent-based products, the surface must be completely free of moisture before application.

## Uses

TOPCOAT<sup>®</sup> Precote is a required step for treatment of corrugated asbestos panels providing optimum adhesion of TOPCOAT<sup>®</sup> Membrane. After application of Precote, the surface will be slightly tacky and will provide an excellent base for the application of TOPCOAT<sup>®</sup> Membrane. Do not apply at temperatures below 42°F. Substrate temperatures must be below 120°F when applying product.

## Advantages

- Excellent primer and sealer for all areas of Transite panels
- Used to bind loose and friable surfaces
- Will leave the roof surface "tacky" and ready to provide a solid substrate for adhesion of TOPCOAT<sup>®</sup> Membrane

## For Application Questions

Contact GAF Technical Services at 1-800-766-3411 or visit [gaf.com](http://gaf.com).

**Note:** Repair leaks promptly to avoid adverse effects, including mold growth.

## TOPCOAT<sup>®</sup> PRECOTE TECHNICAL DATA

Application Rate:	0.75 to 1 gallon /100 sq. ft.
Application Method:	Roller or brush
Application Temperature (air, surface):	42° - 120°F
Drying Time (75°F, 50% RH):	Approximately 30 minutes
Wet Mil Thickness:	12-16 (0.012"-0.016")
Dry Mil Thickness:	3-4 (0.003"-0.004")
Total Solids (by weight):	28.4% + 1%
Total Solids (by volume):	24.0% +/- 1%
Specific Gravity:	0.86 g/cc
Weight per Gallon:	7.2 ± 0.5 lbs
Viscosity (75°F):	200 ± 100 cps
Storage:	Store in well-ventilated area at 50° - 80°F; protect from freezing
Shelf Life:	1 year
Clean-Up:	Xylene, Toluene

**\*Note: Follow all EPA regulations concerning asbestos.**

LEED<sup>®</sup> Credit Available

State of Florida Approved

