

Cobra® RidgeRunner® Exhaust Vent for Roof Ridge

Remove excess heat and moisture from the attic and protect the roof system from premature deterioration



- Help reduce excessive attic heat and moisture and the risk of ice dams in the winter
- Avoid premature roof system degradation
- Limit the growth of harmful mold and mildew

Cobra® RidgeRunner® Exhaust Vent for Roof Ridge



Benefits:

- **Allows heat and moisture to escape** at the most effective location — the ridge
- **30' (9.1 m) RidgeRunner® roll features** smooth roll-out and reduced spring-back/recoil for installation ease and enhanced finished appearance on the ridge
- **Fully nail-gunnable** plastic roll design — simply roll out and fasten with included corrosion-resistant ring shank coil nails
- **Sleek, low-profile design** with external baffles and internal crush-resistant structure
- **Engineered for durability** with high-impact UV-resistant polymers
- **Model with Weather Fighter® filter** helps resist snow, pine needle, and insect infiltration while avoiding dust clogging — meets the requirements of ICC dust exposure testing.¹ **Non-filtered model also available** in warmer climates.
- **Unique EasyTear® sizing feature** allows you to hand-tear the vent in 12" (305 mm) increments — less cutting and less waste
- **Eligible for up to a Lifetime[†] Limited Warranty**, and it's an eligible accessory product in the Attic Ventilation category of GAF residential enhanced warranties

Balanced Attic Ventilation:

Balanced attic ventilation means an equal amount of air entering and exiting it. The amount of exhaust ventilation must **never** exceed the amount of intake ventilation at the soffits or eaves. GAF recommends a minimum of 1 sq. ft. of net free ventilation for every 300 sq. ft. of attic floor space. Always consult local

building codes for specific ventilation requirements.

How Much Do I Need?

Measure the total square footage of attic floor space and then review the chart below to calculate how much Cobra® RidgeRunner® Exhaust Vent for Roof Ridge is needed:

Total attic sq. footage	Recommended length of Cobra® RidgeRunner® Exhaust Vent (ft.)	Minimum intake ventilation (net free area in sq. in.)
1,600	31	388
1,900	37	463
2,200	43	533
2,500	48	600
2,800	54	675
3,100	60	750
3,400	66	825

Note: Chart above based on 1/300 rule. Always have a balanced attic ventilation system. In no case should the amount of exhaust ventilation at or near the ridge exceed the amount of intake ventilation at or near the soffits. Visit gaf.com/ventcalculator for more details.



To learn more about the Lifetime Roofing System visit gaf.com/Lifetime



Product details:

Models available for all climates

- Roll size: 11.5' x 30' (292 mm x 9.1 m)
- Model with WeatherFighter® filter available in all areas (non-filtered model available in warm climates less prone to snow)
- For use with 12"- (305 mm) width ridge cap shingles
- 12.5 sq. inches per linear foot (26,458 mm² per linear meter) of net free ventilating area
- Nail gun installation with included 1 3/4" (44 mm) corrosion-resistant ring shank coil nails
- For roof pitches 3:12 to 16:12

Code Approvals & Standards:

- Miami-Dade County Product Control Approved
- State of Florida Approved
- UL ER15072-01
- Texas Department of Insurance Product Evaluation RV-29
- CCMC14083-R (filtered model only)
- UL Listed to ANSI/UL 790 Class C²
- Meets certain FORTIFIED Roof™ requirements. Visit gaf.com/Fortified and current FORTIFIED Home™ Standard available at fortifiedhome.org for details. U.S. only.



1. Warm, moist air escapes attic through **Cobra® RidgeRunner® Exhaust Vent for Roof Ridge** (installed under ridge cap shingles)
2. Fresh air enters attic through intake vent at or near the soffit

[†] Lifetime refers to the length of warranty coverage provided and means as long as the original individual owner(s) of a single-family detached residence [or eligible second owner(s)] owns the property where the qualifying GAF products are installed. For other owners/structures, Lifetime coverage is not applicable. Lifetime coverage on shingles requires the use of GAF Lifetime shingles only. See the *GAF Shingle & Accessory Limited Warranty* for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products. Lifetime coverage on shingles and accessories requires the use of any GAF Lifetime shingle and at least 3 qualifying GAF Accessories. See the *GAF Roofing System Limited Warranty* for complete coverage and restrictions. For installations not eligible for the *GAF Roofing System Limited Warranty*, see the *GAF Shingle & Accessory Limited Warranty*. Visit gaf.com/LRS for qualifying GAF products.

¹ Tested in accordance with ICC AC132, Section 4.2.

² Refer to UL Online Certification Directory for actual assemblies.

We protect what matters most™

