

EverGuard® PVC-Coated **GAF SpeedTite™ Drain**



Description:

EverGuard® PVC-Coated SpeedTite™ Roof Drains are part of GAF single-ply roofing system accessories that provide contractors easy-to-install, factory-built details.

- Factory-built accessories can help reduce risk of leaks and callbacks
- Uniform aesthetic look

Application:

These drains are designed for use with GAF EverGuard® PVC and PVC XK single-ply membranes. They can be installed using conventional techniques on mechanically attached, fully adhered EverGuard® PVC roofing systems. See published application and specifications manual for detailed instructions.

Product Information:

Mechanical seal and drop-in-ready packaging help speed installation for the EverGuard® PVC-Coated SpeedTite™ Roof Drain. It offers built-in vortex breaker technology for improved flow performance.

- GAF SpeedTite™ mechanical seal (patent pending) can be made watertight in seconds without using any tools
- Hand-tightened seal activator creates a symmetrical watertight connection
- One-piece seamless body provides strength and durability
- Extra-large flange allows positive attachment of roof flashing membrane
- Heavy-duty cast aluminum strainer dome and clamping ring
- Exceeds ANSI/SPRI RD1 requirements for back flow prevention for improved flow performance
- PVC-coated flange for hot-air weld flashing
- Two sizes available to be compatible with 3" (76 mm) or 4" (102 mm) inside diameter plumbing lines

SPECIFICATIONS

Drain body	11 ga. 0.125" (3.18 mm) spun aluminum	
Flange	17½" (445 mm) diameter with sump area	
Stem	10" (254 mm) length	

SHIPPING

SPECIFICATIONS

**3" (76 mm)
compatible**

**4" (102 mm)
compatible**

Drains per carton	1	1
Weight per carton	8.5 lb. (3.86 kg)	8.9 lb. (4.04 kg)
Cartons per pallet	20	20

PRODUCT SKUS

	8523T	8523U
--	-------	-------



Visit **gaf.com**

For additional information, contact GAF Design Services at 1-877-423-7663 or designservices@gaf.com

We protect what matters most™

GAF