



DRILL-TEC™ 2 3/8" DF

BARBED SEAM PLATES

**Drill-Tec™ 2 3/8" DF
Barbed Seam
Plate**



Description

Drill-Tec™ 2 3/8" DF Barbed Seam Plates are made of Galvalume® coated steel. The Drill-Tec™ 2 3/8" DF Barbed Seam Plate is used to attach single-ply membranes to the substrate. The round design provides an even distribution of loads and eliminates sharp corners that can damage the insulation or membrane. These plates are designed to be used with Drill-Tec™ #14 DF Fasteners and Drill-Tec™ #15 DF Fasteners.

For full application instructions please consult the applicable specification manual for the system being installed — available at gaf.com. For applications not listed or other questions, please contact Technical Support at 1-877-GAF-ROOF or technicalquestions@gaf.com.

Note: Galvalume® is a registered trademark of BIEC International Inc. and some of its licensed producers.

Code Approvals



Refer to FM RoofNav.com for actual assemblies

Physical Data

Drill-Tec™ 2 3/8" DF Barbed Seam Plates

Application: Attach EverGuard® membrane to the substrate.
Fastener: Drill-Tec™ #14 DF and #15 DF Fasteners.

Product Data

Plate	Application	Diameter	Packaging Box	Weight
2 3/8" DF Barbed Seam Plate	Membrane	2 3/8" (60.3 mm)	1,000	36 lb. (16.32 kg)