



DRILL-TEC™ 2.4"

BARBED SEAM AND SCOOP SEAM PLATES

Drill-Tec™ 2.4"
Barbed Seam
Plate



Drill-Tec™ 2.4"
Scoop Seam Plate



Description

Drill-Tec™ 2.4" Barbed Seam Plates and Drill-Tec™ 2.4" Scoop Seam Plates are made of Galvalume® coated steel. The round design provides an even distribution of loads and eliminates sharp corners that can damage the insulation or membrane. These plates are designed to be used with Drill-Tec™ #14 HD Fasteners and Drill-Tec™ #15 EHD Fasteners. The Drill-Tec™ 2.4" Barbed Seam Plate and Drill-Tec™ 2.4" Scoop Seam Plate are used to attach single-ply membranes to the substrate.

Please refer to GAF-published application instructions for complete installation requirements. For applications not listed or with questions, please contact Technical Support at 1-800-766-3411 or technicalquestions@gaf.com.

Note: Galvalume® is a registered trademark of BIEC International Inc. and some of its licensed producers.

Product Data

| Plate | Application | Diameter | Packaging Box | Weight |
|------------------------|-------------|----------------|---------------|-------------------|
| 2.4" Barbed Seam Plate | Membrane | 2.4" (60.3 mm) | 1,000 | 50 lb. (22.68 kg) |
| 2.4" Scoop Seam Plate | Membrane | 2.4" (60.3 mm) | 1,000 | 45 lb. (20.41 kg) |

Code Approvals



Physical Data

Drill-Tec™ 2.4" (60.3 mm) Barbed Seam Plate

Application: Attaches EverGuard® membrane to the substrate.

Fastener: Drill-Tec™ #14 HD and #15 EHD Fasteners.

Drill-Tec™ 2.4" (60.3 mm) Scoop Seam Plate

Application: Attaches EverGuard® membrane to the substrate.

Fastener: Drill-Tec™ #14 HD and #15 EHD Fasteners.